

Assessment of National Benefits from Retrofitting Existing Single-Family Homes with Ground Source Heat Pump Systems

Final Report

June 2010

Prepared by

Xiaobing Liu

Energy and Transportation Science Division

Sponsored by

Resources for the Future (RFF)



DOCUMENT AVAILABILITY

Reports produced after January 1, 1996, are generally available free via the U.S. Department of Energy (DOE) Information Bridge.

Web site <http://www.osti.gov/bridge>

Reports produced before January 1, 1996, may be purchased by members of the public from the following source.

National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
Telephone 703-605-6000 (1-800-553-6847)
TDD 703-487-4639
Fax 703-605-6900
E-mail info@ntis.gov
Web site <http://www.ntis.gov/support/ordernowabout.htm>

Reports are available to DOE employees, DOE contractors, Energy Technology Data Exchange (ETDE) representatives, and International Nuclear Information System (INIS) representatives from the following source.

Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831
Telephone 865-576-8401
Fax 865-576-5728
E-mail reports@osti.gov
Web site <http://www.osti.gov/contact.html>

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Energy and Transportation Science Division

**Assessment of National Benefits from Retrofitting Existing Single-Family Homes with
Ground Source Heat Pump Systems**

Final Report

June 2010

Prepared by
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831-6283
Managed by
UT-BATTELLE, LLC
For the
U.S. DEPARTMENT OF ENERGY
Under contract DE-AC05-00OR22725

Contents

List of Acronyms and Abbreviations	vii
Acknowledgments.....	viii
Abstract	ix
Executive Summary	x
1. Introduction.....	1
2. Overview of GHP Technology and GHP Industry in the United States.....	2
2.1 Basics of GHP Technology.....	2
2.2 Current Status of GHP Industry in the United States	5
2.3 Key Barriers Preventing Rapid Growth of the GHP industry in the United States .	7
3. Assessment of National Benefits from GHP Retrofit	10
3.1 Energy Use of Typical SH-SC-WH Systems in Existing Single-Family Homes..	10
3.2 State-of-the-Art GHP System	13
3.3 Reference Building	13
3.4 Calculation Tool	13
3.5 Calculation Procedure for Energy Savings and CO ₂ Emissions Reduction	14
3.6 Calculation Procedure for Summer Peak Electrical Demand Reduction	16
3.7 Selected Locations for Energy Analysis	17
3.8 Estimated Benefits	20
3.8.1 Energy Savings	20
3.8.2 Reductions in CO ₂ Emissions	24
3.8.3 Reductions in Summer Peak Electrical Demand	27
3.8.4 Savings in Consumer Energy Expenditures.....	27
4. Valuing Investment in GHP Systems Compared to Alternatives	30
4.1 Energy Consumption and Expenditures of Alternative Retrofit Solutions.....	31
4.2 Retrofit Cost of the GHP System and Alternatives	34
4.3 Variables and Parameters Used in the Calculations	35
4.4 Predicted NPV from Investment in GHP Retrofits.....	36
4.5 Predicted Levelized Cost of Energy Efficiency of GHP Retrofits	38
4.6 Uncounted Values and Benefits.....	39
5. Conclusions.....	41
6. References.....	41
Appendix A – Description of Reference Single-family Home.....	44
Appendix B – Description of GeoDesigner Software.....	45
Appendix C – Population-Weighted Average of Energy Consumptions, CO ₂ Emissions, and Energy Expenditures of each Typical SH-SC-WH System in each Census Region..	48

List of Acronyms and Abbreviations

AC	Air conditioning
AFUE	Annual fuel utilization efficiency
ASHP	Air-source heat pump
ASHRAE	American Society of Heating, Refrigerating, and Air Conditioning Engineers
BEDB	DOE-EIA Buildings Energy Data Book
BHEX	Borehole heat exchanger
COP	Coefficient of performance
DoD	U.S. Department of Defense
DOE	U.S. Department of Energy
DOE-BT	U.S. Department of Energy Building Technologies Program
EER	Energy efficiency ratio
EF	Energy factor
EIA	DOE Energy Information Administration
GHG	Greenhouse gas
GHP	Geothermal heat pump
IECC	International Energy Conservation Code
LPG	Liquified petroleum gas
NOAA	National Oceanic and Atmospheric Administration
NREL	National Renewable Energy Laboratory
ORNL	Oak Ridge National Laboratory
RECS	Residential Energy Consumption Survey
SC	Space cooling
SFH	Single-family home
SH	Space heating
UESC	Utility energy services contract
WH	Water heating
ZEH	Zero-energy home

Acknowledgments

This work was sponsored by Resources for the Future (RFF). Special thanks to RFF's Senior Fellow, Margaret Walls, for her support. The author also wishes to acknowledge Patrick Hughes, John Shonder, and Erica Atkin at Oak Ridge National Laboratory for their valuable input.

Abstract

This report first briefly reviews geothermal heat pump (GHP) technology and the current status of the GHP industry in the United States. Then it assesses the potential national benefits, in terms of energy savings, reduced summer peak electrical demand, consumer energy cost savings, and reduced CO₂ emissions from retrofitting the space heating, space cooling, and water heating systems in existing U.S. single-family homes with state-of-the-art GHP systems. The investment for retrofitting typical U.S. single-family homes with state-of-the-art GHP systems is also analyzed using the metrics of net present value and levelized cost.

Executive Summary

The geothermal heat pump (GHP) is a proven technology capable of significantly reducing energy use and summer peak electrical demand in buildings. However, there are only about 600,000 GHP units installed in the United States (Rybach 2005). Given the 111.1 million households in the United States, even if all the 600,000 GHP units were installed in residential buildings, they would account for only slightly more than 0.5% of the entire U.S. housing stock. The barriers preventing rapid growth of GHP applications have been identified as high first cost to consumers, lack of knowledge and/or trust in GHP system benefits, limited design and installation infrastructure for GHP systems, and lack of new technologies and techniques (Hughes 2008).

This report assesses the potential national benefits of retrofitting U.S. single-family homes with state-of-the-art GHP systems at various penetration rates. The benefits considered include energy savings, reduced summer electrical peak demand, consumer utility bill savings, and reduced CO₂ emissions. The assessment relied heavily on energy consumption and other data obtained from the Residential Energy Consumption Survey (RECS) conducted by DOE's Energy Information Administration (EIA). It also considered relative differences in energy consumption between a state-of-the-art GHP system and existing residential space-heating, space-cooling, and water-heating (SH-SC-WH) systems, which were determined with a well-established energy analysis program for residential SH-SC-WH systems. The impacts of various climate and geological conditions, as well as efficiency and market share of existing residential SH-SC-WH systems, have been taken into account in the assessment.

The analysis shows that replacing all SH-SC-WH systems in existing U.S. single-family homes with properly designed, installed, and operated state-of-the-art GHP systems would yield the following benefits annually:

- Savings of **4.2 quadrillion (quad) Btu in primary energy**, a **45.1%** reduction in primary energy consumption associated with SH-SC-WH in existing U.S. single-family homes
- Reduction of **271.9 million metric tons in CO₂ emissions**, a **45.3%** reduction in CO₂ emissions associated with SH-SC-WH in existing U.S. single-family homes
- Savings of **\$52.2 billion in energy expenditures**, a **48.2%** reduction in energy costs for SH-SC-WH in these homes
- Reduction of **202.1 gigawatt in summer peak electrical demand**, a **55.2%** reduction in summer peak electrical demand for space cooling in existing U.S. single-family homes

Though it may not be feasible to realize the above maximum benefits, the benefits of GHP retrofits are also significant even at lower market penetration rates, as shown in the following table.

Table E-1. Potential benefits of retrofitting existing U.S. single-family homes with state-of-the-art GHP systems at various market penetration rates.

Market Penetration Rate of GHP Retrofit	20%	40%	60%	80%	100%
Primary Energy Savings [Quad BTU]	0.8	1.7	2.5	3.3	4.2
Percentage Savings	9.0%	18.0%	27.1%	36.1%	45.1%
CO2 Emissions Reduction [MM ton]	54.3	108.7	163.0	217.3	271.7
Percentage Savings	9.1%	18.1%	27.2%	36.2%	45.3%
Summer Peak Electrical Demand Reduction [GW]	40.4	80.8	121.3	161.7	202.1
Percentage Savings	11.0%	22.1%	33.1%	44.2%	55.2%
Energy Expenditures Savings [Billion \$]	10.4	20.9	31.3	41.7	52.2
Percentage Savings	9.6%	19.3%	28.9%	38.5%	48.1%

The investment for retrofitting typical U.S. single-family homes with state-of-the-art GHP systems is evaluated using the metrics of net present value and levelized cost. It was determined that state-of-the-art GHP systems will yield a positive net present value (NPV) over a 20-year period at current market prices for installed systems, and without any financial incentives, when the discount rate is lower than 8%. The levelized-cost analysis shows that saving energy with the GHP retrofit is cheaper than generating and delivering electricity to residences when the discount rate is lower than 8%. The currently enacted federal tax credits for 30% of the installed cost of a GHP system (valid through 2016) were not considered in this analysis. Had they been, investments in state-of-the-art GHP systems would be beneficial even at higher discount rates. Other factors not considered in this analysis include the residual value of the ground loop heat exchanger (ground loops outlive the building and several generations of heat pumps), and financial values from reduced CO₂ emissions and summer peak electrical demand.

1. Introduction

Buildings present one of the best opportunities for cost-effectively reducing energy consumption and limiting CO₂ emissions. The long-term goal of the U.S. Department of Energy's Building Technologies Program (DOE-BTP) is to maximize the cost-effective energy efficiency in buildings. DOE-BTP's vision for achieving the goal involves, among other things, reducing the energy used by residential energy service equipment (equipment providing space heating and cooling and water heating) by 50% compared with today's best common practice.

The geothermal heat pump (GHP) is a proven technology capable of significantly reducing energy use and peak electrical demand in buildings and could play an important role in reaching the goal. According to the latest Residential Energy Consumption Survey (RECS) by the U.S. Energy Information Administration (EIA), 71.8% of the 111.1 million U.S. households (the Census Bureau's statistical estimate of the number of occupied housing units in 2005) live in single-family homes, most of which have space conditioning and/or water heating (DOE-EIA 2009). These 79.8 million single-family homes are excellent candidates for GHP retrofits because

- an average of about 73% of the delivered energy consumed in single-family homes is used for space conditioning and water heating — about 43% for space heating alone (DOE-EIA 2009);
- most of the conventional space conditioning and water heating equipment used in existing single-family homes is approaching the end of its expected service life and needs to be replaced; and
- most U.S. single-family homes have front and/or back yards, which usually have more than enough space for installing vertical or horizontal ground heat exchangers for GHP systems.

However, there are only about 600,000 GHP units installed in the United States (Rybach 2005). Given the 111.1 million households in the United States, even if all 600,000 GHP units were installed in residential buildings, they would account for only slightly more than 0.5% of the entire U.S. housing stock. Obviously, there is huge potential for the growth of GHP installations in residential buildings.

A study recently conducted by Oak Ridge National Laboratory (Hughes 2008) concludes from a survey of U.S. GHP industry experts that high first costs to consumers, lack of knowledge and/or trust in GHP system benefits, limited design and installation infrastructures for GHP systems, and lack of new technologies and techniques are the most significant barriers to the wide application of GHP. The study recommends a series of actions to overcome these barriers. One of the two highest-priority actions is to conduct an independent assessment of the national benefits (energy, demand, cost, CO₂ emissions, jobs) achievable from implementing a maximum deployment strategy for GHP systems, including comparisons with other supply- and demand-side options in terms of when benefits could be achieved, national investment required, and probability of success.

This report gives a brief overview of GHP technology and the current status of the GHP industry in the United States (section 2), and assesses the “technical potential” for total energy savings, reduced summer electrical peak demand, consumer utility bill savings, and reduced CO₂ emissions from retrofitting SH-SC-WH systems in existing U.S. single-family homes with state-of-the-art GHP systems. The study methodology is described in section 3. An analysis of the economics of GHP retrofits is presented in section 4.

2. Overview of GHP Technology and GHP Industry in the United States

This section of the report presents the basics of GHP technology and an overview of the current status of the GHP industry in the United States. Key barriers preventing rapid growth of the GHP industry in the United States identified by a recent survey of GHP industry experts are summarized. Hughes (2008) provides a more detailed and comprehensive overview of GHP technology and the GHP industry.

2.1 Basics of GHP Technology

GHP is a relatively new technology for space conditioning and water heating. The biggest difference between GHP and conventional space conditioning and water heating systems is that instead of rejecting heat from buildings to the ambient air (in cooling mode) and extracting heat from fossil fuel combustion, electricity, or the ambient air (in space heating and/or water heating modes), a GHP rejects heat to (in cooling mode) or extracts heat from (in space heating and/or water heating modes) various ground resources, including the earth, surface water, recycled gray water, sewage treatment plant effluent, storm water retention basins, harvested rainwater, and water from subsurface aquifers — either alone or in combination with conventional heat addition/rejection devices in a hybrid configuration.

Since the ground resources usually have a more favorable temperature than the ambient air for the heating/cooling operation of the vapor-compression refrigeration cycle, GHP systems can operate with much higher energy efficiency than conventional air-source heat pumps, especially for heating operation in cold climates. GHP systems harvest the free and renewable energy (solar, geothermal, and heat removed from the built environment) stored in various ground resources to provide space heating and/or water heating, which is a reverse of the vapor-compression cycle widely used in air conditioning and refrigeration. GHPs thus significantly reduce energy consumption and greenhouse gas (GHG) emissions compared with conventional equipment, such as furnaces and boilers using natural gas, oil, or electricity.

A study by the U.S. Environmental Protection Agency (EPA) comparing the major heating, ventilating, and air-conditioning (HVAC) options for residential applications determined that GHP was the most energy-efficient and environmentally benign option (EPA 1993). The Nobel-Prize-winning Intergovernmental Panel on Climate Change specifically identified GHP as a solution that is “economically feasible under certain circumstances” in continental and cold climates (IPCC 2007a, see Table 6.1) and cited cases in which total electricity use decreased by a third (IPCC 2007a, p. 404) and heating energy use decreased by 50 to 60%. The potential of GHP to reduce nonrenewable energy use was also highlighted in a 2007 United Nations Environmental Programme

report (UNEP 2007). A 2008 American Physical Society report (2008) referred to GHP systems (pp. 56 and 73) as being among the options that could help the U.S. building sector achieve the goal of using no more primary energy in 2030 than in 2008, rather than increasing energy use by 30% by 2030 as currently projected. Enhanced use of ground energy sources and heat sinks at the building or community level is highlighted as a promising option in the 2008 report designed to establish the federal R&D agenda for buildings issued by the Executive Office of the President's National Science and Technology Council (2008).

A GHP system is made up of three major components: a water-source heat pump (WSHP) unit operable over an extended range of entering-fluid temperatures (referred to as the GHP unit hereafter); a ground heat exchanger designed for available ground resources; and a circulation system to deliver cold or warm air or water to the built environment and circulate the liquid heat transfer medium (water or aqueous anti-freeze solution) through the GHP unit and the ground heat exchanger.

Small packaged or split water-to-air heat pump units are most popularly used in the GHP systems in the United States. An alternative configuration that may be more economical in some situations is a small or large water-to-water heat pump unit. Rather than directly delivering cold or hot air to spaces as the water-to-air heat pump does, a water-to-water heat pump delivers chilled or hot water to various types of zone terminals. Today's GHP systems move 3 to 5 times more energy between the building and the ground sources than they consume in doing so. If there were sufficient motivation, the GHP industry could increase this multiplier effect to 6 – 8 by integrating the most advanced commercially available components and technologies into their heat pumps, such as variable-speed compressors, variable-refrigerant-flow systems, and special refrigerants.

Figure 1 illustrates a number of options for the ground heat exchanger. The vast majority of GHP systems in the United States are installed with closed-loop heat exchangers using high-density polyethylene (HDPE) pipe buried in the earth in either a vertical or horizontal configuration. The closed-loop technology permits GHPs to be applied effectively almost anywhere. The HDPE piping technology has been perfected by the natural gas industry for collecting underground natural gas in production fields and distributing it to customers.




Fig. 1 Typical options for ground heat exchanger used in GHP systems.

The ground heat exchanger can be designed at the scale of a community or a single building and can serve new construction or retrofits of existing communities or buildings. In many areas, it may be possible to serve the modest heating, cooling, ventilation, water heating, and refrigeration loads of highly efficient new homes and commercial buildings with efficient heat pumps coupled to ground loops placed in construction excavations, without any extra digging or drilling whatsoever.

GHP technology is not the same technology as geothermal power production, in which the extreme heat of subsurface geological processes is used to produce steam and ultimately to generate electricity. Nor is it the same as the direct use of geothermal heat, in which moderate-temperature geothermal sources such as hot springs are used directly to heat greenhouses, aquaculture ponds, and other agricultural facilities. Whereas geothermal power production and direct use of geothermal heat can be economical at only a limited number of locations in the United States, GHP systems can be used almost

anywhere. GHP systems use the only renewable energy resource that is available at every building's point of use, on-demand, that cannot be depleted (assuming proper design), and are potentially affordable in all 50 states.

Technologies aiming at cost reduction and performance improvement of GHP systems are being pursued in the United States and even more aggressively in some European and Asian countries. Topics being researched include the following.

- Integrated GHP units serving multiple purposes including heating, cooling, water heating, and dehumidification
- Design tools and models for ground heat exchangers installed in the excavations and/or foundations needed to construct buildings
- Design tools for surface-water heat pump systems
- Design guidelines and tools for hybrid GHPs
- Single-well groundwater supply and return systems
- Compact horizontal loops reloaded via heat exchange with exhaust air
- Devices to test borehole heat exchanger installation quality
- New-generation technology for in-situ ground thermal property testing

2.2 Current Status of GHP Industry in the United States

The U.S. GHP industry was started in the early 1970s by entrepreneurs including contractors and manufacturers. Currently, it is made up of manufacturers of water-source heat pumps (WSHPs), HDPE piping and fittings, circulating pumps, and specialty components, as well as a design infrastructure, an installation infrastructure, and various trade allies, most notably electric utilities.

A small group of manufacturers — including ClimateMaster (a unit of LSB Industries), Florida Heat Pump (a unit of Bosch), WaterFurnace International, Inc., and Trane (a unit of Ingersoll Rand) — are believed to produce most GHP units, supplemented by McQuay International (a unit of Daikin), Mammoth, and several regional manufacturers. Most of these manufacturers produce WSHP units not only for the GHP market but also for water loop heat pump (WLHP) systems, which use more conventional cooling towers and boilers in place of ground heat exchangers. Other major brands such as Carrier participate in the WLHP and GHP markets by sourcing WSHP units from other manufacturers.

In addition to serving GHP applications, HDPE pipe is used in oil production fields and for natural gas collection and distribution, sewerage collection, potable water distribution, landfill gas collection, industrial applications, and irrigation. The manufacturing base is large and well established. It is believed that Performance Pipe (a unit of Chevron–Philips), ISCO Industries, and Centennial Plastics are the largest suppliers of HDPE to the GHP market.

Circulating pumps, propylene glycol antifreeze, plate heat exchangers, fluid coolers, and many other products used in GHP systems are already mass-produced to serve markets much larger than the GHP market.

The specialty products unique to the GHP market—such as flow centers, flush carts, purge pumps, pump stations, headers, vaults, hose kits, thermally enhanced grouts, specialty installation equipment, and surface water immersion heat exchangers—are generally made by relatively small regional firms.

Although there are a significant number of competent and experienced designers of residential and commercial GHP systems, especially those with vertical-bore ground heat exchangers, the number is still a small percentage of HVAC design engineers. Similarly, experienced and competitive installation infrastructures for ground heat exchangers are in short supply and exist only in portions of some states.

During the 30-year history of the U.S. GHP industry, many modest but successful GHP programs sponsored by the electric utilities have boosted the GHP industry in some localities. The contribution of GHP systems in reducing summer peak electrical demand and improving the load factor of the electricity supply is the main reason for electric utility support of the GHP industry. Until the 1990s, GHP technology got attention from policymakers in Washington, D.C., and two notable federal GHP programs — the National Earth Comfort Program and the Federal Energy Management Program GHP technology-specific program (Hughes and Pratsch 2002) — were initiated to demonstrate GHP technology, mobilize the GHP market, and provide financial and technical support for implementing GHP systems. These utility and federal GHP programs were successful in increasing public awareness of GHP technology and increasing GHP unit shipments, as well as collecting hard data proving the benefits of GHP systems in terms of reducing maintenance and energy costs.

Though the United States was the world leader in GHP technology and still has the largest installed base of GHP systems — approximately 600,000 units in 2005 (Rybach 2005) — the GHP market share in the United States is much smaller than in some European countries. A 2005 review of the global market status of GHP systems estimated that Sweden, Denmark, Switzerland, and some other countries ranked higher on a per capita basis (Rybach 2005) than the United States. Owing to supportive government policies, the GHP market is growing rapidly in Asia, especially in China and South Korea. It is believed that the European and Asian markets have currently exceeded U.S. markets in annual shipments of GHP units.

Although the GHP industry in the United States remains small, it is better positioned for rapid growth than at any time during the past 30 years in many respects. Federal and state governments in the United States are giving strong incentives to support the development and application of energy efficiency and renewable energy technologies, among which GHP has been given high priority. Tax credits for home and business owners investing in GHP systems were enacted in October 2008 through 2016. Since 2007, rural electric cooperatives have been able to obtain loans from the U.S. Department of Agriculture Rural Utilities Service with terms of up to 35 years, at the cost of government funds, to provide the outside-the-building portion of GHP systems to customers in exchange for a tariff on the utility bill. The tariff would be more than offset by the GHP system's energy cost savings. In December 2007 Congress directed the General Services Administration (GSA) to establish a program to accelerate the use of more cost-effective energy-saving technologies and practices in GSA facilities, starting with lighting and GHPs. A growing number of states offer tax credits or other incentives for GHP systems (listed on the

Database of State Incentives for Renewable Energy [DSIRE] Web site). In October 2009, DOE awarded a total of \$63 million in American Recovery and Reinvestment Act funds to support the sustainable growth of the U.S. GHP industry through actions in three areas:

1. Demonstrating innovative business and financing strategies and/or technical approaches designed to overcome barriers to commercialization of GHPs
2. Gathering data, conducting analysis, and developing tools to assist consumers in determining project feasibility and achieving lowest-life-cycle-cost GHP applications
3. Creating a national certification standard for the GHP industry to increase consumer confidence in the technology, reduce the potential for improperly installed systems, and ensure product quality and performance

GHP units have been improved significantly in energy efficiency, noise level, and lifespan. Most GHP unit manufacturers have well-established supply chains and paths to market. There also have been improvements in the design and energy analysis of GHP systems, including (1) a design tool sponsored by the American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE) for hybrid GHP systems (Hackel 2009) and (2) the integration of improved representations of vertical bore ground heat exchangers and GHP systems in eQUEST, a DOE-2-based building energy analysis program that is credible but also relatively easy to use (Liu 2008).

The diverse segments of the GHP industry are better able to work with each other as a cohesive whole than ever before. The installed base of systems is much larger today and can serve to inform best practices. The most important trade allies of the GHP industry, electric utilities, are better able now to focus on peak load reduction and improved load factor, two key GHP system benefits, than they were in 1993 when utility restructuring was looming.

The infrastructure of support organizations is also much stronger now than it was in 1993. The International Ground Source Heat Pump Association (IGSHPA), which represents all segments of the industry, has matured. It provides the nation's only major conferences and exhibitions totally focused on GHP technology, and it has developed respected training for drillers and installers. The Geothermal Heat Pump Consortium has been reconstituted as an advocacy and government relations organization sponsored by the GHP industry. ASHRAE Technical Committee TC 6.8, Geothermal Energy Utilization, has made great strides in developing the technical foundation for sound design of commercial GHP systems. The National Ground Water Association (NGWA) is more engaged than ever. National laboratory and university expertise persists, even though there have never been reliable funding sources to sustain GHP programs at these institutions.

2.3 Key Barriers Preventing Rapid Growth of the GHP industry in the United States

ORNL recently conducted an informal survey of a group of GHP industry experts to identify the barriers to rapid growth of the U.S. GHP industry (Hughes 2008). The survey identified the following barriers in order of priority (1 being the most important):

Tier 1

1. High first cost of GHP systems to consumers

Tier 2

2. Lack of consumer knowledge of and/or trust in GHP system benefits
3. Lack of policymaker and regulator knowledge of and/or trust in GHP system benefits
4. Limitations in GHP design and business planning infrastructure
5. Limitations in GHP installation infrastructure

Tier 3

6. Lack of new technologies and techniques to improve GHP system cost/performance

The multiple tiers are included to indicate that barriers 2–5 had essentially the same level of support among survey participants, whereas barrier 1 was perceived as being of greater importance and barrier 6 of lesser importance than 2 through 5. A bit of a surprise was that most of these barriers are the same as those identified in surveys conducted decades ago. As early as 1994, the National Earth Comfort Program (GHPC 1994) had identified first cost, confidence or trust in the technology, and design and installation infrastructure as the primary barriers to the growth of the GHP industry.

How high is the first cost of GHP systems to consumers? The Department of Defense — perhaps the largest single customer for GHP retrofit projects — reports that in 2006 dollars, housing and commercial retrofits cost \$4,600 and \$7,000 per ton respectively, and simple paybacks in the two regions with the most installed capacity averaged 8.6 to 12 years (DoD 2007). Retrofits in the private sector would likely be similar in cost and payback. New construction has the potential to be more economical because part of the first cost is offset by the avoided cost of the displaced conventional system, but simple paybacks exceeding 5 years are still common. First cost and long payback periods clearly limit GHP system acceptance in many markets. Currently in commercial markets, GHPs are primarily limited to institutional customers (e.g., federal, state, and local governments; K-12 schools) that take the life-cycle view. In residential markets, GHPs are limited to a small subset of newly constructed homes that the builder plans to occupy and thus wants to equip with the best available system, and to home retrofits in which the owner plans to occupy the premises long enough to justify the investment. In all of these cases, the building owner must have the financial wherewithal to use his/her own credit to finance the system.

What contributes to the high first cost of GHP systems? The ground heat exchanger (especially the vertical bore system, the one most often used) is the major reason for the high first cost. The cost of the ground heat exchanger usually makes up more than half the total cost of a GHP system. The GHP unit also contributes to the high first cost — currently 50–100% more expensive at retail than air-source heat pump units of comparable capacity and component quality. Several other interacting factors, which are directly or indirectly related to the tier 2 and 3 barriers listed above, also contribute to the high first cost. Figure 2 illustrates the factors that affect the first cost of GHP systems and their relationships to the identified barriers.



Fig. 2. Factors that affect the first cost of GHP systems and their relationships.

As shown in Figure 2, all the barriers result in a small market share for GHP systems in the United States. In turn, the small market share perpetuates the barriers because the GHP technology is almost invisible to the general public and thus unattractive to design, business planning, and installation professionals. The lack of public awareness and trust directly leads to low motivation to invest in and support the GHP industry. The limited design, business planning, and installation infrastructure implies that many HVAC professionals are not experienced with GHP applications. As a result, research and development (R&D) for GHP technology has been limited, and few new technologies and techniques have been developed. Without a substantial contribution from R&D, neither significant cost reduction and performance enhancement nor significant improvements in public awareness/trust and design/installation infrastructure are likely.

Given the large proportion of unmotivated consumers and inexperienced design/installation professionals, the GHP supply chain (original equipment manufacturers, distributors, dealers) must educate them and even provide extra technical assistance for the design and installation of GHP systems. These extra selling and training costs are included in the prices of GHP products. That partially explains why GHP units are currently 50–100% more expensive at retail than air-source heat pump units of comparable capacity and component quality. Of course, the relatively small shipment

volume and the low motivation for investment and support (i.e., R&D to reduce cost and improve performance) also contribute to the relatively high cost of GHP units.

Inexperienced designers tend to oversize GHP systems and/or add excessive backup capacity to provide a larger safety margin, but doing so unnecessarily increases their cost. Lack of experience and competition in ground heat exchanger installation is another reason for the high first cost of GHP systems. Typically, the cost of installing a ground heat exchanger for a project can be 100–400% higher when an experienced and competitive installation infrastructure is not available.

Figure 2 shows that the GHP industry is trapped in a cycle of high first cost leading to small market leading to high first cost. To escape this cycle, the high first cost of GHP systems to consumers must be reduced to a level more competitive with other technologies.

3. Assessment of National Benefits from GHP Retrofit

The benefits achievable from retrofitting existing single-family homes with GHP systems depend on many factors, including the characteristics of the building itself (construction, orientation, insulation level, air tightness, etc.), energy efficiency and fuel type of existing SH-SC-WH systems (e.g. natural gas, heating oil, propane/liquefied propane gas, and electricity), occupants' lifestyle, and many other location-sensitive parameters, such as:

- climate conditions,
- cost of fuels used by the existing SH-SC-WH systems,
- primary energy (e.g. coal, natural gas, nuclear, and various types of renewable energy) consumption and CO₂ emissions associated with generating electricity and delivering it to building sites, which depends on the energy mix for electricity generation at a particular location, and
- primary energy consumption and CO₂ emissions associated with harvesting and delivering fossil fuels to building sites.

To accurately predict the magnitude of the national potential of benefits from retrofitting U.S. single-family homes with GHP systems, all of these factors need to be properly accounted for.

3.1 Energy Use of Typical SH-SC-WH Systems in Existing Single-Family Homes

EIA (Energy Information Agency) keeps track of the annual delivered energy¹ consumption of the entire U.S. residential sector through national area-probability-sample surveys², and the results are published regularly by DOE in the Buildings Energy Data

¹ Energy delivered to building without adjustment for energy consumed for producing and delivering the energy.

² The survey collected data from 4,382 households sampled at random using a complex, multistage, area-probability design to represent 111.1 million U.S. households, the Census Bureau's statistical estimate for all occupied housing units in 2005. Data were obtained from residential energy suppliers for each unit in the sample to produce the Consumption & Expenditures data.

Book. Data for SH-SC-WH system types and associated annual energy use for existing U.S. single-family homes have been extracted from the Public Use Microdata Files of the latest residential energy consumption survey (RECS 2005). Table 1 summarizes the SH-SC-WH systems that are most popularly used in existing U.S. single-family homes and their energy efficiencies (EIA 1978-1997, DOE BTP 2005). The number of single-family homes that use a particular SH/SC/WH system in each U.S. census region and corresponding annual consumption of delivered energy are presented in Table 2.

Table 1. Typical SH-SC-WH systems used in U.S. single-family homes.

Energy Services	Existing Systems/Equipments	Rated Efficiencies
Space Heating	Air source heat pump (ASHP)	3.2 COP ⁽ⁱ⁾
	Electric heater	100 EF ⁽ⁱⁱ⁾
	Natural gas fired furnace/boiler	80 AFUE ⁽ⁱⁱⁱ⁾
	Propane/LPG fired furnace/boiler	80 AFUE
	Heating oil fired furnace/boiler	80 AFUE
Space Cooling	Central air conditioner (CAC) / ASHP	10 SEER ^(iv)
	Room air conditioner (RAC)	7.7 SEER
	Combination of CAC and RAC	7.7 – 10 SEER
Water Heating	Electric heater	88 EF
	Natural gas heater	58 EF
	Propane/LPG heater	58 EF
	Heating oil heater	58 EF

- i. COP stands for Coefficient of Performance, which is the ratio of heating energy provided to the space to the electric energy consumed when operating at standard conditions. The COP of the air source heat pump listed in the table is measured at standard, mild weather (47°F) rating conditions.
- ii. EF stands for Energy Factor, which indicates a water heater's overall energy efficiency based on the amount of hot water produced per unit of fuel consumed over a typical day.
- iii. AFUE stands for Annual Fuel Utilization Efficiency, which is the ratio of the annual amount of heat actually delivered to the amount of fuel supplied to the furnace.
- iv. SEER stands for Seasonal Energy Efficiency Ratio, which is the average annual cooling efficiency of an air-conditioning or heat pump system determined with a standard methodology and assuming typical weather.

Table 2. Number of single-family homes with SH/SC/WH in each census region and corresponding annual consumption of delivered energy (based on data from RECS Public Use Microdata Files).

Census Region	SH/SC/WH System Types	Number of Existing Single-Family Homes	Percentage of Existing Single-Family Homes in a Region that Use Various Systems for SH/SC/WH	Delivered Energy Consumed for SH/SC/WH by Existing Single-family Homes in each Census Region (from RECS 2005)	Percentage of Delivered Energy Consumption in a Region by Single-Family Homes with Various Systems for SH/SC/WH
		Millions	-	Billion Btu	-
Northeast	Space Heating	13.0	100%	1,036,111.4	100%
	Electric Heat Pump	0.18	1.4%	1,869.5	0.2%
	Electric Heater	0.70	5.4%	15,518.5	1.5%
	Natural gas	7.19	55.5%	545,290.1	52.6%
	Propane/LPG	0.36	2.8%	26,577.9	2.6%
	Fuel Oil	4.54	35.0%	446,855.4	43.1%
	Space Cooling	11.1	100%	55,800.7	100%
	Central air conditioner	4.95	44.4%	35,651.9	63.9%
	Room air conditioner	6.10	54.8%	18,571.6	33.3%
	Both central and room AC	0.10	0.9%	1,577.1	2.8%
	Water Heating	13.3	100%	322,149.1	100%
	Electric	2.93	22.0%	27,361.2	8.5%
	Natural gas	7.08	53.1%	187,572.4	58.2%
	Propane/LPG	0.52	3.9%	17,533.8	5.4%
	Fuel Oil	2.80	21.0%	89,681.8	27.8%
	Regional Sub-Total	37.4		1,414,061.2	
Midwest	Space Heating	19.4	100%	1,220,359.0	100%
	Electric Heat Pump	0.69	3.6%	9,528.2	0.8%
	Electric Heater	1.38	7.1%	38,577.5	3.2%
	Natural gas	14.91	76.9%	1,007,014.8	82.5%
	Propane/LPG	1.71	8.8%	110,737.9	9.1%
	Fuel Oil	0.69	3.6%	54,500.6	4.5%
	Space Cooling	18.6	100%	125,209.6	100%
	Central air conditioner	14.64	78.6%	111,213.5	88.8%
	Room air conditioner	3.62	19.4%	11,851.6	9.5%
	Both central and room AC	0.36	1.9%	2,144.4	1.7%
	Water Heating	23.0	109%	450,429.6	100%
	Electric	5.56	24.2%	60,561.6	13.4%
	Natural gas	13.60	59.3%	348,376.4	77.3%
	Propane/LPG	0.99	4.3%	40,391.1	9.0%
	Fuel Oil	2.80	21.0%	1,100.5	0.2%
	Regional Sub-Total	61.0		1,795,998.2	
South	Space Heating	28.0	100%	692,639.8	100%
	Electric Heat Pump	6.04	21.6%	39,701.8	5.7%
	Electric Heater	8.02	28.6%	105,666.7	15.3%
	Natural gas	11.58	41.3%	416,522.4	60.1%
	Propane/LPG	1.92	6.9%	91,162.6	13.2%
	Fuel Oil	0.45	1.6%	39,586.2	5.7%
	Space Cooling	28.0	100%	443,245.8	100%
	Central air conditioner	22.71	81.0%	388,678.9	87.7%
	Room air conditioner	4.64	16.5%	39,477.2	8.9%
	Both central and room AC	0.70	2.5%	15,089.7	3.4%
	Water Heating	31.9	112%	521,217.2	100%
	Electric	16.67	52.3%	166,429.5	31.9%
	Natural gas	11.53	36.2%	314,584.5	60.4%
	Propane/LPG	0.86	2.7%	35,951.7	6.9%
	Fuel Oil	2.80	21.0%	4,251.5	0.8%
	Regional Sub-Total	87.9		1,657,102.8	
West	Space Heating	15.6	100%	473,587.2	100%
	Electric Heat Pump	0.79	5.1%	5,269.7	1.1%
	Electric Heater	2.72	17.4%	31,853.3	6.7%
	Natural gas	11.26	72.0%	378,182.1	79.9%
	Propane/LPG	0.66	4.2%	35,628.5	7.5%
	Fuel Oil	0.21	1.3%	22,653.6	4.8%
	Space Cooling	9.5	100%	78,108.0	100%
	Central air conditioner	7.74	81.7%	73,231.3	93.8%
	Room air conditioner	1.49	15.8%	3,433.9	4.4%
	Both central and room AC	0.24	2.5%	1,442.8	1.8%
	Water Heating	19.5	107%	409,343.8	100%
	Electric	3.41	17.5%	39,301.4	9.6%
	Natural gas	12.56	64.5%	338,378.5	82.7%
	Propane/LPG	0.72	3.7%	30,576.5	7.5%
	Fuel Oil	2.80	21.0%	1,087.4	0.3%
	Regional Sub-Total	44.6		961,039.0	
Total				5.8 Quad Btu	

3.2 State-of-the-Art GHP System

The state-of-the-art GHP system presented in this study consists of a packaged water-to-air GHP unit with a two-stage scroll compressor and variable-speed electronically commutated motor (ECM) fan, a properly sized and highly energy efficient loop fluid circulator, and a properly designed and installed vertical borehole ground heat exchanger. The nominal cooling efficiency of the two-stage GHP unit is EER³ 18.2 at full capacity and EER 27 at 76% of full capacity. The nominal heating efficiency of the two-stage GHP unit is COP 4 at full capacity and COP 4.5 at 76% of full capacity⁴.

The ground heat exchanger is sized to maintain the fluid temperature from the ground loop [the entering fluid temperature (EFT) to the GHP unit] within the range of 30°F - 95°F for given building loads, ground thermal properties, and the undisturbed ground temperature.

The state-of-the-art GHP system can contribute to water heating through use of a desuperheater. Desuperheaters apply the waste heat produced whenever the GHP runs for space cooling to the water heater (usually an electric storage-type water heater). In this study, the efficiency of the electric water heater is assumed to be EF 88.

3.3 Reference Building

Given the vast number and wide variation of homes in the United States, it is not practical to model each of the existing single-family homes. On the other hand, the relative difference in annual energy consumption between the state-of-the-art GHP system and existing SH-SC-WH systems for providing the same energy service depends more on the characteristics of the compared systems, weather, and geological conditions than the building itself. Therefore, one reference building representing typical U.S. single-family homes (including internal loads from lighting, appliances, cooking, and occupants) is used in this study to calculate the relative difference in annual energy consumption between the state-of-the-art GHP system and existing SH-SC-WH systems. The description of this reference building is provided in Appendix A.

3.4 Calculation Tool

The annual delivered energy consumption of the state-of-the-art GHP system and typical existing SH-SC-WH systems was calculated with GeoDesigner, a well-established energy analysis program developed by ClimateMaster, Inc.

GeoDesigner uses the ASHRAE bin analysis method to calculate the energy consumption of GHP and other residential SH-SC-WH systems. Compared with more sophisticated hourly energy simulation programs, bin analysis is less accurate in estimating the impacts of weather elements (i.e., solar, wind, precipitation, etc.) and the heat gain from activities inside the building (i.e., lighting, cooking, showering, etc.) on the building heating/cooling loads. Bin analysis also limits the capability for more detailed analysis of electrical demand of the building and more accurate calculation of ground heat exchanger temperatures.

³ EER is the cooling capacity (in Btu/hour) of the unit divided by its electrical input (in watts) at standard conditions.

⁴ The COP and EER are measured at AHRI/ISO/ASHRAE/ANSI 13256-1 rating conditions: for cooling at full capacity, EFT is 77°F; for heating at full capacity, EFT is 32°F.

However, while there are some discrepancies in the predicted total energy consumption of particular SH-SC-WH systems, the relative difference in energy consumption between the state-of-the-art GHP system and the existing SH-SC-WH systems predicted by GeoDesigner and the more sophisticated programs are fairly close.

Since, as described below, it is the relative difference in annual energy consumption between different SH-SC-WH systems that is needed for this study, and considering the advantages of GeoDesigner, including user-friendly interfaces and reports, robust and fast calculations, and capability for performing energy analysis for a wide range of residential SH-SC-WH systems, GeoDesigner was selected for this study. The more detailed description of the algorithms, capabilities, and limitations of GeoDesigner are given in Appendix B.

3.5 Calculation Procedure for Energy Savings and CO₂ Emissions Reduction

The efficiencies of air source heat pumps and air conditioners are affected by the outdoor ambient temperature, and the efficiency of a GHP system is influenced by the fluid temperature from the ground heat exchanger, which is determined by the building heating and cooling loads, the size of the ground heat exchanger, and geological conditions (i.e., the ground thermal properties) where the system is installed. Therefore, to obtain an estimate of the regional average of the relative difference in annual energy consumption between the GHP system and existing SH-SC-WH systems, different weather and geological conditions within the region were accounted for in this study. As a simplification, it is assumed that the weather and undisturbed ground temperatures are identical across a climate zone within a census region. Ground thermal properties values that are very common in the United States are used for all the climate zones (representing the typical thermal properties of granite, limestone, and sandstone with 1.4 Btu/hr-ft-F thermal conductivity and 0.04 ft²/hr thermal diffusivity). We first calculated the delivered energy consumed annually by each of the typical existing SH-SC-WH systems and the state-of-the-art GHP system for providing the same SH-SC-WH service, in each climate zone within a particular census region. Then we used the population associated with each climate zone as a weighting factor to calculate the regional average of annual delivered energy consumption for each of the compared systems. Finally we computed the regional relative difference in annual delivered energy consumption between the state-of-the-art GHP system and each of the existing SH-SC-WH systems.

The procedure and formulas used for estimating the annual national potential savings in delivered energy from retrofitting U.S. single-family homes with GHP systems is described in the following.

Step 1:

Calculate the peak heating and cooling loads of the reference building at various locations that represent major climate zones with each of the four U.S. census regions.

Step 2:

Calculate the annual delivered energy consumption of each compared SH-SC-WH system with GeoDesigner based on the peak heating and cooling loads determined in Step 1 and the associated weather and geological conditions.

Step 3:

Calculate the regional average of annual delivered energy consumption of a particular SH-SC-WH system serving the reference building with Equation 1.

$$Avg_Sys_DE(j,k) = \frac{\sum_{i=1}^n Sys_DE(i,j,k) \cdot CZ(i,k)}{\sum_{i=1}^n CZ(i,k)} \quad (Eq. 1)$$

where

$Avg_Sys_DE(j,k)$ is the average annual delivered energy consumption of SH-SC-WH system j in census region k ;

$Sys_DE(i,j,k)$ is the annual delivered energy consumption of SH-SC-WH system j in climate zone i of census region k ;

$CZ(i,k)$ is the population in climate zone i of census region k ; and

n is the number of major climate zones in census region k .

Step 4:

Calculate the regional average relative differences in annual delivered energy consumption between the state-of-the-art GHP system and each of the typical existing SH-SC-WH systems with Equation 2.

$$RD_DE(j,k) = \frac{Avg_Sys_DE(j,k) - Sys_DE_GHP(k)}{Avg_Sys_DE(j,k)} \quad (Eq. 2)$$

where

$RD_DE(j,k)$ is the regional average relative difference in annual delivered energy consumption between the state-of-the-art GHP system and SH-SC-WH system j in census region k ; and

$Sys_DE_GHP(k)$ is the average annual energy consumption of the state-of-the-art GHP system in census region k .

Step 5:

Calculate the annual savings in delivered energy from GHP retrofits in a particular region with Equation 3.

$$Reg_DE(k) = \sum_{j=1}^m SFHS_DE(j,k) \cdot Penetration \cdot RD_DE(j,k) \quad (\text{Eq. 3})$$

where

$Reg_DE(k)$ is the annual savings in delivered energy in census region k ;

$SFHS_DE(j,k)$ is the annual delivered energy consumed by existing SH-SC-WH system j in census region k ;

$Penetration$ is the assumed fraction of existing U.S. single-family homes captured by GHP retrofits; and

m is the number of existing SH-SC-WH systems used in U.S. single-family homes.

Step 6:

Calculate the national potential savings in delivered energy from retrofitting existing U.S. single-family homes with the state-of-the-art GHP system with Equation 4.

$$National_DE = \sum_{k=1}^4 Reg_DE(k) \quad (\text{Eq. 4})$$

Following this procedure, the national potential of savings/reductions in energy expenditure, primary energy consumption, and CO₂ emissions were also estimated. In these calculations, the annual delivered energy consumption of each compared SH-SC-WH system was replaced with the associated energy expenditure, primary energy consumption, or CO₂ emissions using corresponding regional utility rates, conversion factors between delivered and primary energy, and emissions factors of various fuels used by the compared SH-SC-WH systems.

3.6 Calculation Procedure for Summer Peak Electrical Demand Reduction

Since there is no documented data available for regional or national summer peak electrical demand of residential buildings, the potential reduction in peak demand from GHP retrofits is estimated from the bin analysis data generated by GeoDesigner.

In general, the summer peak electrical demand of single-family homes is coincident with the peak electrical demand for space cooling. Therefore, the reduction in summer peak electrical demand is determined in this study as the reduction of electrical demand for space cooling at its peak. The calculation is expressed in Equation 5.

$$PEDFSC = \frac{kWh_MaxTemp}{Hr_MaxTemp \times Fraction_HP} \quad (\text{Eq. 5})$$

Where

$PEDFSC$ is the peak electrical demand for space cooling, kW;

kWh_MaxTem_i is the electrical energy consumed for space cooling when outdoor ambient temperature is within the highest temperature bin of a particular location, kWh;

Hr_MaxTem_i is the number of hours when outdoor ambient temperature is within the highest temperature bin of a particular location, hour; and

$Fraction_HP$ is the percentage of Hr_MaxTem_i when the heat pump runs.

The above calculated peak electrical demand for cooling is further normalized by dividing it with the coincident peak cooling load (expressed in tons) of the reference building at the particular location, in kW/ton.

The regional average summer peak electrical demand for space cooling for the state-of-the-art GHP system and typical existing SC systems are determined by applying the population weighting factor of each climate zone to the normalized electrical demands calculated for each climate zone within a particular census region. The regional total summer peak electrical demand for space cooling is the product of three variables:

- the average normalized summer peak electrical demand for space cooling per household in a census region (kW/ton);
- the average cooling tonnage per household in a census region (ton); and
- the total number of households in a census region that use space cooling.

3.7 Selected Locations for Energy Analysis

The 2004 International Energy Conservation Code (IECC) Climate Zones for the U.S. are used in this study. These climate zones were developed based on analysis of the 4775 National Oceanic and Atmospheric Administration (NOAA) weather sites and statistical analysis of regional information, and are used in ASHRAE standards 90.1 and 90.2, the ASHRAE Advanced Energy Design Guide Series, and DOE's Building America program. Figure 3 shows the 2004 IECC Energy Code Climate Zones, which are assigned using county boundaries.




Fig. 3. 2004 IECC Climate Zones of the United States.




Fig. 4. U.S. Census Regions and Divisions.

Comparing the U.S. census regions map in Figure 4 with the climate zones in Figure 3 shows that each census region covers multiple climate zones. Table 3 lists the percentages of population in each climate zone in each census region. Where the percentage of the population in a climate zone is very low (less than 5% of the total population in the census region), that climate zone is omitted from the calculations. One location (a city) was selected to represent each of the 14 climate zones included in this study.

Table 3. Percentage of population in each climate zone within each of the U.S. Census Regions.

Climate Zones	U.S. Census Regions			
	Northeast	Midwest	South	West
1A	-	-	4.0%	1.9%
1B	-	-	-	-
2A	-	-	29.2%	-
2B	-	-	0.4%	7.4%
3A	-	-	35.1%	-
3B	-	-	1.8%	44.7%
3C	-	-	-	11.5%
4A	40.1%	18.8%	28.2%	-
4B	-	-	0.5%	2.6%
4C	-	-	-	11.8%
5A	51.5%	60.2%	0.9%	-
5B	-	-	-	16.4%
5C	-	-	-	-
6A	8.3%	18.4%	-	-
6B	-	-	-	3.5%
7A	0.1%	2.5%	-	-
7B	-	-	-	0.3%
8A	-	-	-	-
8B	-	-	-	-

The peak heating and cooling loads for the reference building at each of the 14 locations were calculated using eQUEST, a DOE-2–based building energy analysis program, and the results are listed in Table 4. These peak heating and cooling loads, along with other user-specified parameters (i.e., location/bin-weather data, SH-SC-WH system type and efficiency, number of occupants, hot water temperature, etc.), are used by GeoDesigner to calculate the annual delivered energy consumption of various SH-SC-WH systems serving the building.

Table 4. Peak heating and cooling loads for the reference building in 14 representative locations (cities).

Census Region	Climate Zone	City	State	Peak Heating Load	Peak Cooling Load (Tot)	Peak Cooling Load (Sen)
				Btu/Hr	Btu/Hr	Btu/Hr
NorthEast	4A	Philadelphia	PA	29,204	20,650	15,116
NorthEast	5A	Boston	MA	32,695	15,307	11,358
NorthEast	6A	Bangor	ME	44,309	18,761	14,165
MidWest	4A	Kansas City	MO	33,772	25,286	18,358
MidWest	5A	Chicago	IL	40,490	20,092	14,627
MidWest	6A	Minneapolis	MN	45,452	18,191	13,570
South	2A	Houston	TX	22,004	25,113	18,458
South	3A	Atlanta	GA	26,436	23,884	18,152
South	4A	Nashville	TN	35,860	24,489	18,489
West	2B	Phoenix	AZ	14,191	26,598	25,215
West	3B	Sacramento	CA	15,890	19,388	17,120
West	3C	San Francisco	CA	14,734	13,589	12,828
West	4C	Portland	OR	25,756	15,076	12,860
West	5B	Denver	CO	40,817	15,118	15,118

3.8 Estimated Benefits

The potential benefits from retrofitting U.S. single-family homes with the state-of-the-art GHP system were estimated using the procedures described in previous sections. The estimated national potential for each of the four major benefits of GHP retrofits — energy savings, reductions in CO₂ emissions, avoided summer peak electrical demand, and energy expenditure savings — all at various market penetration rates, are presented in the following sections. The energy consumption, CO₂ emissions, summer peak electrical demand, and energy expenditures of each of the compared SH/SC/WH systems at each of the 14 representative locations, as well as the population-weighted average for each census region, are listed in Appendix C.

3.8.1 Energy Savings

The estimated regional and national potential savings in delivered energy are presented in Table 5. Columns 3 and 4 summarize the regional average of the delivered energy consumed by the state-of-the-art GHP system and the existing SH-SC-WH systems, respectively, for providing the same energy services to the reference building. As described previously, these regional averages have taken into account the impacts of typical weather, geological conditions, and population distribution within the region. Column 5 lists the regional average of savings in delivered energy from retrofitting the existing SH-SC-WH systems with the state-of-the-art GHP system. Column 6 expresses the savings as a percentage of the delivered energy consumed by the existing SH-SC-WH systems. Column 7 provides the regional total of delivered energy consumed for SH-SC-WH at single-family homes, which is obtained from Public Use Microdata Files of the latest residential energy consumption survey (RECS 2005). Columns 8 through 12 present the estimated regional potential in savings of delivered energy at various market penetration rates.

Table 5. National savings of delivered energy from GHP retrofits for existing U.S. single-family homes

Census Region	SH-SC-WH System Types	Regional Average Delivered Energy Cons. by Existing SH-SC-WH System in Reference Building	Regional Average Delivered Energy Cons. by GHP System in Reference Building	Regional Average Savings of Delivered Energy in Reference Building	Percentage Savings of Delivered Energy from GHP Retrofit	Regional Delivered Energy Cons. for SH-SC-WH in All Single-Family Homes (RECS 2005)	Estimated Regional Potential in Savings of Delivered Energy				
							20% Market Penetration Rate for GHP Retrofit	40% Market Penetration Rate for GHP Retrofit	60% Market Penetration Rate for GHP Retrofit	80% Market Penetration Rate for GHP Retrofit	100% Market Penetration Rate for GHP Retrofit
		Million Btu	Million Btu	Million Btu	%	Trillion Btu	Trillion Btu	Trillion Btu	Trillion Btu	Trillion Btu	Trillion Btu
Northeast	Space Heating					1,036.1	170.9	341.8	512.6	683.5	854.4
	Electric Heat Pump	41.5	14.4	27.1	65.3%	1.9	0.2	0.5	0.7	1.0	1.2
	Electric Heater	56.5	14.4	42.1	74.5%	15.5	2.3	4.6	6.9	9.3	11.6
	Natural gas	78.4	14.4	64.0	81.7%	545.3	89.1	178.1	267.2	356.3	445.3
	Propane/LPG	76.3	14.4	61.9	81.2%	26.6	4.3	8.6	12.9	17.3	21.6
	Fuel Oil	89.0	14.4	74.7	83.9%	446.9	74.9	149.9	224.8	299.8	374.7
	Space Cooling					55.8	8.5	16.9	25.4	33.8	42.3
	Central air conditioner	5.8	1.5	4.3	73.7%	35.7	5.3	10.5	15.8	21.0	26.3
	Room air conditioner	7.5	1.5	6.0	79.7%	18.6	3.0	5.9	8.9	11.8	14.8
	Both central and room AC	6.6	1.5	5.1	77.1%	1.6	0.2	0.5	0.7	1.0	1.2
	Water Heating					322.1	37.4	74.8	112.1	149.5	186.9
	Electric	16.7	10.4	6.3	37.8%	27.4	2.1	4.1	6.2	8.3	10.3
	Natural gas	26.0	10.4	15.7	60.2%	187.6	22.6	45.2	67.8	90.4	113.0
	Propane/LPG	25.3	10.4	15.0	59.1%	17.5	2.1	4.1	6.2	8.3	10.4
	Fuel Oil	25.5	10.4	15.1	59.4%	89.7	10.7	21.3	32.0	42.6	53.3
	Regional Total SH-SC-WH					1,414.1	216.7	433.4	650.2	866.9	1,083.6
Midwest	Space Heating					1,220.4	195.8	391.6	587.4	783.2	979.0
	Electric Heat Pump	56.6	18.2	38.5	67.9%	9.5	1.3	2.6	3.9	5.2	6.5
	Electric Heater	67.1	18.2	48.9	72.9%	38.6	5.6	11.3	16.9	22.5	28.1
	Natural gas	93.2	18.2	75.0	80.5%	1,007.0	162.1	324.3	486.4	648.5	810.7
	Propane/LPG	90.6	18.2	72.5	80.0%	110.7	17.7	35.4	53.1	70.8	88.5
	Fuel Oil	105.8	18.2	87.6	82.8%	54.5	9.0	18.1	27.1	36.1	45.1
	Space Cooling					125.2	17.2	34.5	51.7	69.0	86.2
	Central air conditioner	8.3	2.6	5.6	68.1%	111.2	15.1	30.3	45.4	60.6	75.7
	Room air conditioner	10.7	2.6	8.1	75.4%	11.9	1.8	3.6	5.4	7.2	8.9
	Both central and room AC	9.5	2.6	6.9	72.2%	2.1	0.3	0.6	0.9	1.2	1.5
	Water Heating					450.4	53.0	106.0	159.1	212.1	265.1
	Electric	18.6	11.1	7.5	40.4%	60.6	4.9	9.8	14.7	19.6	24.4
	Natural gas	29.1	11.1	18.0	61.8%	348.4	43.1	86.2	129.3	172.4	215.5
	Propane/LPG	28.3	11.1	17.2	60.7%	40.4	4.9	9.8	14.7	19.6	24.5
	Fuel Oil	28.5	11.1	17.4	61.0%	1.1	0.1	0.3	0.4	0.5	0.7
	Regional Total SH-SC-WH					1,796.0	266.1	532.1	798.2	1,064.2	1,330.3
South	Space Heating					692.6	112.7	225.4	338.0	450.7	563.4
	Electric Heat Pump	20.5	7.8	12.8	62.2%	39.7	4.9	9.9	14.8	19.7	24.7
	Electric Heater	33.8	7.8	26.1	77.1%	105.7	16.3	32.6	48.9	65.1	81.4
	Natural gas	47.0	7.8	39.3	83.5%	416.5	69.6	139.1	208.7	278.2	347.8
	Propane/LPG	45.8	7.8	38.0	83.0%	91.2	15.1	30.3	45.4	60.6	75.7
	Fuel Oil	53.4	7.8	45.7	85.5%	39.6	6.8	13.5	20.3	27.1	33.8
	Space Cooling					443.2	54.9	109.8	164.8	219.7	274.6
	Central air conditioner	14.7	5.7	9.0	61.0%	388.7	47.4	94.8	142.2	189.6	237.0
	Room air conditioner	19.1	5.7	13.4	70.0%	39.5	5.5	11.0	16.6	22.1	27.6
	Both central and room AC	16.9	5.7	11.2	66.0%	15.1	2.0	4.0	6.0	8.0	10.0
	Water Heating					521.2	57.5	114.9	172.4	229.8	287.3
	Electric	15.6	9.3	6.4	40.7%	166.4	13.5	27.1	40.6	54.1	67.7
	Natural gas	24.4	9.3	15.1	62.0%	314.6	39.0	78.0	117.1	156.1	195.1
	Propane/LPG	23.7	9.3	14.5	60.9%	36.0	4.4	8.8	13.1	17.5	21.9
	Fuel Oil	23.9	9.3	14.6	61.2%	4.3	0.5	1.0	1.6	2.1	2.6
	Regional Total SH-SC-WH					1,657.1	225.1	450.1	675.2	900.2	1,125.3
West	Space Heating					473.6	77.5	155.0	232.5	310.0	387.5
	Electric Heat Pump	20.7	8.2	12.5	60.2%	5.3	0.6	1.3	1.9	2.5	3.2
	Electric Heater	34.0	8.2	25.7	75.7%	31.9	4.8	9.6	14.5	19.3	24.1
	Natural gas	47.0	8.2	38.8	82.5%	378.2	62.4	124.7	187.1	249.5	311.8
	Propane/LPG	45.8	8.2	37.5	82.0%	35.6	5.8	11.7	17.5	23.4	29.2
	Fuel Oil	53.4	8.2	45.1	84.5%	22.7	3.8	7.7	11.5	15.3	19.2
	Space Cooling					78.1	9.6	19.2	28.7	38.3	47.9
	Central air conditioner	8.1	3.2	4.9	60.8%	73.2	8.9	17.8	26.7	35.6	44.5
	Room air conditioner	10.6	3.2	7.4	69.8%	3.4	0.5	1.0	1.4	1.9	2.4
	Both central and room AC	9.3	3.2	6.2	65.9%	1.4	0.2	0.4	0.6	0.8	1.0
	Water Heating					409.3	45.1	90.2	135.3	180.4	225.5
	Electric	16.0	10.7	5.4	33.6%	39.3	2.6	5.3	7.9	10.6	13.2
	Natural gas	25.1	10.7	14.4	57.5%	338.4	38.9	77.8	116.7	155.6	194.5
	Propane/LPG	24.4	10.7	13.7	56.2%	30.6	3.4	6.9	10.3	13.8	17.2
	Fuel Oil	24.5	10.7	13.9	56.6%	1.1	0.1	0.2	0.4	0.5	0.6
	Regional Total SH-SC-WH					961.0	132.2	264.4	396.5	528.7	660.9
National Total of Delivered Energy Savings [Quad Btu]							0.8	1.7	2.5	3.4	4.2
Percentage Savings							14.4%	28.8%	43.2%	57.7%	72.1%

As shown in Table 5, while the annual consumption of delivered energy for a particular SH/SC/WH system varied significantly among the census regions, the relative differences

between the state-of-the-art GHP system and the existing SH/SC/WH systems were not very sensitive to the census region. Compared with SH/SC/WH systems typically used in existing single-family homes, the state-of-the-art GHP system consumed 60% – 86% less delivered energy for space heating, 60% – 80% less delivered energy for space cooling, and 34% - 62% less delivered energy for water heating. If all SH/SC/WH systems in existing U.S. single-family homes are replaced with state-of-the art GHP systems, it is estimated that 4.2 Quad Btu of delivered energy will be saved each year, which equals 72.1% of all delivered energy currently consumed for SH-SC-WH in U.S. single-family homes. However, if only 20% of U.S. single-family homes are retrofitted with the state-of-the-art GHP system, the savings of delivered energy is about 0.8 Quad Btu, which is a 14.4% reduction from current consumption levels.

By converting the delivered energy consumption data (both the calculated delivered energy consumption for SH-SC-WH in the reference building and the documented delivered energy consumption for all existing U.S. single-family homes) to the associated primary energy consumption with the conversion factors listed in Table 6, the national potential of savings in annual primary energy consumption is estimated, as shown in Table 7. The primary energy conversion factors for electricity and fossil fuels were adopted from a recent report from National Renewable Energy Laboratory (NREL 2007). While the primary energy conversion factors for other fossil fuels are independent of the location where the delivered energy is consumed, the primary energy conversion factor for electricity depends on the energy portfolio for electricity generation for the particular location, and these portfolios will likely include more renewable/green energy in the future. However, since the primary energy conversion factors for electricity at each census region were not available when this study was conducted, the 2005 national average of the primary energy conversion factor for electricity was used.

Table 6. Source energy factors for fuel or electricity delivered to buildings.

Fuel	Conversion Factor
Natural Gas	1.092
Propane	1.151
Heating Oil	1.158
Electricity	3.365

As shown at the bottom of Table 7, a total of 3.8 Quad Btu of primary energy, which corresponds to 41.1% of primary energy currently consumed for SH-SC-WH in existing U.S. single-family homes, could be saved each year by retrofitting all existing U.S. single-family homes with state-of-the-art GHP systems. The savings of primary energy is linearly correlated to the market penetration rate of GHP retrofits.

Since the primary energy conversion factor for electricity is larger than that for fossil fuels, the savings in primary energy for space heating and water heating is lower than the savings in delivered energy. The primary energy consumption for water heating actually increased when existing water heaters fired with fossil fuels were replaced with electric water heaters assisted with GHP unit desuperheaters. If by policy the existing water heaters fired with fossil fuels were not replaced with desuperheater-assisted electric water

heaters, the maximum savings of primary energy from GHP retrofits rises from 3.8 Quad Btu to **4.2 Quad Btu**, which is **45.1%** of primary energy currently consumed for SH-SC-WH in existing U.S. single-family homes.

Table 7. National savings of primary energy from GHP retrofits for existing U.S. single-family homes

Census Region	SH-SC-WH System Types	Regional Average Primary Energy Cons. by Existing SH-SC-WH System in Reference Building	Regional Average Primary Energy Cons. by GHP System in Reference Building	Regional Average Savings of Primary Energy Cons. in Reference Building	Percentage Savings of Primary Energy Cons. from GHP Retrofit	Regional Primary Energy Cons. for SH-SC-WH in All Single-Family Homes (RECS 2005)	Estimated Regional Potential in Savings of Primary Energy Cons.				
							20% Market Penetration Rate for GHP Retrofit	40% Market Penetration Rate for GHP Retrofit	60% Market Penetration Rate for GHP Retrofit	80% Market Penetration Rate for GHP Retrofit	100% Market Penetration Rate for GHP Retrofit
		Million Btu	Million Btu	Million Btu	%	Trillion Btu	Trillion Btu	Trillion Btu	Trillion Btu	Trillion Btu	Trillion Btu
Northeast	Space Heating					1,202.0	122.7	245.5	368.2	491.0	613.7
	Electric Heat Pump	139.5	48.4	91.2	65.3%	6.3	0.8	1.6	2.5	3.3	4.1
	Electric Heater	190.0	48.4	141.6	74.5%	52.2	7.8	15.6	23.4	31.1	38.9
	Natural gas	88.4	48.4	40.0	45.3%	595.5	53.9	107.8	161.8	215.7	269.6
	Propane/LPG	91.5	48.4	43.1	47.2%	30.6	2.9	5.8	8.7	11.5	14.4
	Fuel Oil	108.4	48.4	60.1	55.4%	517.5	57.3	114.7	172.0	229.3	286.7
	Space Cooling					187.8	28.5	56.9	85.4	113.8	142.3
	Central air conditioner	19.5	5.1	14.3	73.7%	120.0	17.7	35.4	53.0	70.7	88.4
	Room air conditioner	25.3	5.1	20.1	79.7%	62.5	10.0	19.9	29.9	39.9	49.8
	Both central and room AC	22.4	5.1	17.2	77.1%	5.3	0.8	1.6	2.5	3.3	4.1
	Water Heating					420.9	(7.9)	(15.8)	(23.7)	(31.6)	(39.5)
	Electric	56.1	34.9	21.2	37.8%	92.1	7.0	13.9	20.9	27.9	34.8
	Natural gas	27.9	34.9	-7.0	-25.0%	204.8	(10.2)	(20.5)	(30.7)	(41.0)	(51.2)
	Propane/LPG	28.9	34.9	-5.9	-20.5%	20.2	(0.8)	(1.7)	(2.5)	(3.3)	(4.1)
	Fuel Oil	29.5	34.9	-5.4	-18.3%	103.9	(3.8)	(7.6)	(11.4)	(15.2)	(19.0)
	Regional Total SH-SC-WH					1,810.7	143.3	286.6	429.9	573.2	716.5
Midwest	Space Heating					1,452.1	132.9	265.9	398.8	531.7	664.7
	Electric Heat Pump	190.6	61.1	129.5	67.9%	32.1	4.4	8.7	13.1	17.4	21.8
	Electric Heater	225.8	61.1	164.7	72.9%	129.8	18.9	37.9	56.8	75.7	94.7
	Natural gas	105.0	61.1	43.8	41.8%	1,099.7	91.9	183.7	275.6	367.4	459.3
	Propane/LPG	108.7	61.1	47.6	43.8%	127.5	11.2	22.3	33.5	44.6	55.8
	Fuel Oil	128.8	61.1	67.6	52.5%	63.1	6.6	13.3	19.9	26.5	33.2
	Space Cooling					421.3	58.0	116.0	174.0	232.1	290.1
	Central air conditioner	27.8	8.9	18.9	68.1%	374.2	51.0	101.9	152.9	203.8	254.8
	Room air conditioner	36.1	8.9	27.2	75.4%	39.9	6.0	12.0	18.0	24.1	30.1
	Both central and room AC	31.9	8.9	23.1	72.2%	7.2	1.0	2.1	3.1	4.2	5.2
	Water Heating					632.0	(0.2)	(0.3)	(0.5)	(0.7)	(0.9)
	Electric	62.7	37.4	25.3	40.4%	203.8	16.4	32.9	49.3	65.8	82.2
	Natural gas	31.2	37.4	-6.2	-19.9%	380.4	(15.1)	(30.3)	(45.4)	(60.6)	(75.7)
	Propane/LPG	32.3	37.4	-5.0	-15.5%	46.5	(1.4)	(2.9)	(4.3)	(5.8)	(7.2)
	Fuel Oil	32.9	37.4	-4.4	-13.5%	1.3	(0.0)	(0.1)	(0.1)	(0.1)	(0.2)
	Regional Total SH-SC-WH					2,505.4	190.8	381.6	572.3	763.1	953.9
South	Space Heating					1,094.8	134.2	268.3	402.5	536.7	670.8
	Electric Heat Pump	69.1	26.1	42.9	62.2%	133.6	16.6	33.2	49.8	66.4	83.1
	Electric Heater	113.9	26.1	87.7	77.1%	355.6	54.8	109.6	164.4	219.2	274.0
	Natural gas	53.1	26.1	27.0	50.8%	454.8	46.2	92.5	138.7	185.0	231.2
	Propane/LPG	55.0	26.1	28.9	52.5%	104.9	11.0	22.0	33.1	44.1	55.1
	Fuel Oil	65.2	26.1	39.1	59.9%	45.8	5.5	11.0	16.5	22.0	27.5
	Space Cooling					1,491.5	184.8	369.6	554.4	739.2	924.0
	Central air conditioner	49.6	19.3	30.2	61.0%	1,307.9	159.5	319.0	478.5	638.0	797.6
	Room air conditioner	64.4	19.3	45.0	70.0%	132.8	18.6	37.2	55.8	74.3	92.9
	Both central and room AC	57.0	19.3	37.6	66.0%	50.8	6.7	13.4	20.1	26.8	33.5
	Water Heating					949.9	30.9	61.8	92.6	123.5	154.4
	Electric	52.6	31.2	21.4	40.7%	560.0	45.5	91.1	136.6	182.1	227.7
	Natural gas	26.1	31.2	-5.1	-19.3%	343.5	(13.3)	(26.6)	(39.9)	(53.2)	(66.4)
	Propane/LPG	27.1	31.2	-4.1	-15.0%	41.4	(1.2)	(2.5)	(3.7)	(5.0)	(6.2)
	Fuel Oil	27.6	31.2	-3.6	-12.9%	4.9	(0.1)	(0.3)	(0.4)	(0.5)	(0.6)
	Regional Total SH-SC-WH					3,536.2	349.8	699.7	1,049.5	1,399.4	1,749.2
West	Space Heating					605.1	64.5	128.9	193.4	257.9	322.3
	Electric Heat Pump	69.8	27.8	42.0	60.2%	17.7	2.1	4.3	6.4	8.5	10.7
	Electric Heater	114.3	27.8	86.6	75.7%	107.2	16.2	32.5	48.7	64.9	81.2
	Natural gas	52.7	27.8	24.9	47.3%	413.0	39.1	78.2	117.2	156.3	195.4
	Propane/LPG	54.6	27.8	26.8	49.1%	41.0	4.0	8.1	12.1	16.1	20.1
	Fuel Oil	64.6	27.8	36.8	57.0%	26.2	3.0	6.0	9.0	12.0	15.0
	Space Cooling					262.8	32.2	64.5	96.7	128.9	161.2
	Central air conditioner	27.4	10.7	16.7	60.8%	246.4	30.0	60.0	89.9	119.9	149.9
	Room air conditioner	35.5	10.7	24.8	69.8%	11.6	1.6	3.2	4.8	6.5	8.1
	Both central and room AC	31.5	10.7	20.7	65.9%	4.9	0.6	1.3	1.9	2.6	3.2
	Water Heating					538.2	(18.1)	(36.1)	(54.2)	(72.3)	(90.4)
	Electric	54.0	35.9	18.1	33.6%	132.2	8.9	17.8	26.6	35.5	44.4
	Natural gas	26.8	35.9	-9.0	-33.6%	369.5	(24.9)	(49.7)	(74.6)	(99.4)	(124.3)
	Propane/LPG	27.9	35.9	-8.0	-28.8%	35.2	(2.0)	(4.0)	(6.1)	(8.1)	(10.1)
	Fuel Oil	28.4	35.9	-7.5	-26.4%	1.3	(0.1)	(0.1)	(0.2)	(0.3)	(0.3)
	Regional Total SH-SC-WH					1,406.2	78.6	157.3	235.9	314.5	393.1
National Total of Primary Energy Savings [Quad Btu]							0.8	1.5	2.3	3.1	3.8
Percentage Savings							8.2%	16.5%	24.7%	32.9%	41.2%

3.8.2 Reductions in CO₂ Emissions

By converting the delivered energy consumption data (both the calculated delivered energy consumption for SH-SC-WH in the reference building and the documented

delivered energy consumption for all existing U.S. single-family homes) to the associated CO₂ emissions with the conversion factors listed in Table 8, the national potential reductions in annual CO₂ emissions was determined (Table 9). The emissions factors for electricity and fossil fuels (which account for emissions from both on-site combustion and pre-combustion activities including extracting and delivering the fossil fuels to the point of use) were adopted from a recent report by the National Renewable Energy Laboratory (NREL 2007).

Table 8. Emissions factors for fuels and electricity.

Fuel	CO2 equivalent Emmission Factor	
Natural Gas	150.80	lb per Mcf
Propane	16.06	lb per gallon
Heating Oil	26.90	lb per gallon
Electricity	1.67	lb per kWh

As shown at the bottom of Table 9, 244.6 million metric tons of CO₂ emissions, which accounts for 40.8% of all the CO₂ emissions associated with SH-SC-WH in existing U.S. single-family homes, could be saved each year by GHP retrofits at the 100% market penetration rate.

As with primary energy, the CO₂ emissions associated with water heating increased when existing water heaters fired by fossil fuels were replaced with desuperheater-assisted electric water heaters. If by policy these water heaters were not replaced with desuperheater-assisted electric water heaters, the maximum reduction of CO₂ emissions from GHP retrofits would rise from 244.8 to **271.9 million metric tons**, which is **45.3%** of all CO₂ emissions associated with SH-SC-WH in existing U.S. single-family homes.

Table 9. National total of reduced CO2 emissions from GHP retrofit for existing U.S. single-family homes

Census Region	SH-SC-WH System Types	Regional Average CO2 Emission by Existing SH-SC-WH System in Reference Building	Regional Average CO2 Emission by GHP System in Reference Building	Regional Average Reduction of CO2 Emission in Reference Building	Percentage Reduction of CO2 Emission from GHP Retrofit	Regional CO2 Emission for SH-SC-WH in All Single-Family Homes (RECS 2005)	Estimated Regional Potential in Reduction of CO2 Emission				
							20% Market Penetration Rate for GHP Retrofit	40% Market Penetration Rate for GHP Retrofit	60% Market Penetration Rate for GHP Retrofit	80% Market Penetration Rate for GHP Retrofit	100% Market Penetration Rate for GHP Retrofit
		Lb	Lb	Lb	%	Million Lb	Million Lb	Million Lb	Million Lb	Million Lb	Million Lb
Northeast	Space Heating					179,480.4	18,961.6	37,923.3	56,884.9	75,846.5	94,808.2
	Electric Heat Pump	20,287.6	7,031.2	13,256.3	65.3%	914.8	119.5	239.1	358.6	478.2	597.7
	Electric Heater	27,621.8	7,031.2	20,590.6	74.5%	7,593.3	1,132.1	2,264.1	3,396.2	4,528.3	5,660.4
	Natural gas	12,138.6	7,031.2	5,107.4	42.1%	79,834.7	6,718.1	13,436.3	20,154.4	26,872.6	33,590.7
	Propane/LPG	13,978.7	7,031.2	6,947.5	49.7%	4,659.8	463.2	926.4	1,389.6	1,852.8	2,316.0
	Fuel Oil	17,971.3	7,031.2	10,940.0	60.9%	86,477.8	10,528.7	21,057.4	31,586.0	42,114.7	52,643.4
	Space Cooling					27,303.6	4,138.2	8,276.4	12,414.5	16,552.7	20,690.9
	Central air conditioner	2,829.2	745.0	2,084.3	73.7%	17,444.7	2,570.2	5,140.5	7,710.7	10,281.0	12,851.2
	Room air conditioner	3,674.3	745.0	2,929.4	79.7%	9,087.2	1,449.0	2,897.9	4,346.9	5,795.8	7,244.8
	Both central and room AC	3,251.8	745.0	2,506.8	77.1%	771.7	119.0	238.0	356.9	475.9	594.9
	Water Heating					61,279.9	(978.6)	(1,957.2)	(2,935.8)	(3,914.4)	(4,893.0)
	Electric	8,153.8	5,070.0	3,083.8	37.8%	13,388.0	1,012.7	2,025.3	3,038.0	4,050.7	5,063.4
	Natural gas	3,813.4	5,070.0	(1,256.7)	-33.0%	27,462.1	(1,810.0)	(3,620.0)	(5,430.0)	(7,240.0)	(9,050.0)
	Propane/LPG	4,438.2	5,070.0	(631.9)	-14.2%	3,074.2	(87.5)	(175.1)	(262.6)	(351.1)	(437.7)
	Fuel Oil	4,936.7	5,070.0	(133.3)	-2.7%	17,355.7	(93.7)	(187.5)	(281.2)	(374.9)	(468.7)
	Regional Total SH-SC-WH					268,063.8	22,121.2	44,242.4	66,363.6	88,484.8	110,606.0
Midwest	Space Heating					200,935.8	17,731.8	35,463.7	53,195.5	70,927.4	88,659.2
	Electric Heat Pump	27,711.8	8,887.5	18,824.3	67.9%	4,662.2	633.4	1,266.8	1,900.2	2,533.6	3,167.0
	Electric Heater	32,836.8	8,887.5	23,949.3	72.9%	18,876.2	2,753.4	5,506.9	8,260.3	11,013.8	13,767.2
	Natural gas	14,416.8	8,887.5	5,529.3	38.4%	147,434.8	11,309.2	22,618.3	33,927.5	45,236.6	56,545.8
	Propane/LPG	16,604.4	8,887.5	7,716.9	46.5%	19,415.4	1,804.7	3,609.3	5,414.0	7,218.6	9,023.3
	Fuel Oil	21,346.6	8,887.5	12,459.1	58.4%	10,547.2	1,231.2	2,462.4	3,693.6	4,924.8	6,156.0
	Space Cooling					61,265.7	8,435.8	16,871.6	25,307.5	33,743.3	42,179.1
	Central air conditioner	4,040.4	1,289.7	2,750.7	68.1%	54,417.4	7,409.5	14,819.0	22,228.5	29,638.0	37,047.5
	Room air conditioner	5,247.3	1,289.7	3,957.6	75.4%	5,799.1	874.7	1,749.5	2,624.2	3,499.0	4,373.7
	Both central and room AC	4,643.8	1,289.7	3,354.2	72.2%	1,049.3	151.6	303.2	454.7	606.3	757.9
	Water Heating					87,932.8	(549.9)	(1,099.9)	(1,649.8)	(2,199.8)	(2,749.7)
	Electric	9,112.5	5,434.7	3,677.8	40.4%	29,633.1	2,392.0	4,784.0	7,176.0	9,568.0	11,959.9
	Natural gas	4,261.9	5,434.7	(1,172.8)	-27.5%	51,005.0	(2,807.1)	(5,614.2)	(8,421.3)	(11,228.4)	(14,035.5)
	Propane/LPG	4,960.2	5,434.7	(474.5)	-9.6%	7,081.7	(135.5)	(271.0)	(406.5)	(541.9)	(677.4)
	Fuel Oil	5,517.4	5,434.7	82.7	1.5%	213.0	0.6	1.3	1.9	2.6	3.2
	Regional Total SH-SC-WH					350,134.4	25,617.7	51,235.4	76,853.1	102,470.9	128,088.6
South	Space Heating					155,756.0	18,978.0	37,956.0	56,934.0	75,912.0	94,890.0
	Electric Heat Pump	10,043.7	3,799.3	6,244.4	62.2%	19,426.3	2,415.6	4,831.1	7,246.7	9,662.3	12,077.8
	Electric Heater	16,557.1	3,799.3	12,757.8	77.1%	51,703.3	7,967.8	15,935.7	23,903.5	31,871.4	39,839.2
	Natural gas	7,301.0	3,799.3	3,501.7	48.0%	60,982.1	5,849.7	11,699.3	17,549.0	23,398.6	29,248.3
	Propane/LPG	8,404.0	3,799.3	4,604.7	54.8%	15,983.3	1,751.5	3,503.0	5,254.5	7,006.1	8,757.6
	Fuel Oil	10,804.6	3,799.3	7,005.3	64.8%	7,660.9	993.4	1,986.8	2,980.2	3,973.7	4,967.1
	Space Cooling					216,882.6	26,872.3	53,744.5	80,616.8	107,489.1	134,361.3
	Central air conditioner	7,209.4	2,813.2	4,396.2	61.0%	190,182.8	23,194.4	46,388.8	69,583.2	92,777.6	115,972.0
	Room air conditioner	9,362.9	2,813.2	6,549.7	70.0%	19,316.4	2,702.5	5,405.0	8,107.6	10,810.1	13,512.6
	Both central and room AC	8,286.1	2,813.2	5,473.0	66.0%	7,383.5	975.4	1,950.7	2,926.1	3,901.4	4,876.8
	Water Heating					134,618.6	4,030.2	8,060.3	12,090.5	16,120.7	20,150.9
	Electric	7,644.4	4,536.8	3,107.6	40.7%	81,434.9	6,621.0	13,242.0	19,863.0	26,484.0	33,105.0
	Natural gas	3,574.5	4,536.8	(962.3)	-26.9%	46,057.6	(2,479.9)	(4,959.8)	(7,439.7)	(9,919.6)	(12,399.5)
	Propane/LPG	4,160.1	4,536.8	(376.6)	-9.1%	6,303.3	(114.1)	(228.3)	(342.4)	(456.5)	(570.7)
	Fuel Oil	4,627.4	4,536.8	90.7	2.0%	822.8	3.2	6.4	9.7	12.9	16.1
	Regional Total SH-SC-WH					507,257.2	49,880.4	99,760.9	149,641.3	199,521.7	249,402.2
West	Space Heating					84,164.0	8,756.5	17,512.9	26,269.4	35,025.8	43,782.3
	Electric Heat Pump	10,148.6	4,036.4	6,112.2	60.2%	2,578.5	310.6	621.2	931.8	1,242.4	1,553.0
	Electric Heater	16,624.4	4,036.4	12,588.0	75.7%	15,586.0	2,360.3	4,720.7	7,081.0	9,441.4	11,801.7
	Natural gas	7,233.1	4,036.4	3,196.7	44.2%	55,368.8	4,894.1	9,788.2	14,682.2	19,576.3	24,470.4
	Propane/LPG	8,340.6	4,036.4	4,304.2	51.6%	6,246.7	644.7	1,289.4	1,934.2	2,578.9	3,223.6
	Fuel Oil	10,721.8	4,036.4	6,685.4	62.4%	4,384.0	546.7	1,093.4	1,640.2	2,186.9	2,733.6
	Space Cooling					38,218.7	4,687.0	9,374.0	14,060.9	18,747.9	23,434.9
	Central air conditioner	3,980.4	1,559.2	2,421.2	60.8%	35,832.5	4,359.2	8,718.4	13,077.7	17,436.9	21,796.1
	Room air conditioner	5,169.3	1,559.2	3,610.1	69.8%	1,680.2	234.7	469.4	704.1	938.8	1,173.4
	Both central and room AC	4,574.8	1,559.2	3,015.6	65.9%	706.0	93.1	186.1	279.2	372.3	465.4
	Water Heating					74,343.0	(3,123.7)	(6,247.5)	(9,371.2)	(12,495.0)	(15,618.7)
	Electric	7,848.4	5,214.7	2,633.8	33.6%	19,230.4	1,290.7	2,581.3	3,872.0	5,162.7	6,453.3
	Natural gas	3,669.2	5,214.7	(1,545.4)	-42.1%	49,541.2	(4,173.2)	(8,346.4)	(12,519.7)	(16,692.9)	(20,866.1)
	Propane/LPG	4,270.4	5,214.7	(944.2)	-22.1%	5,360.9	(237.1)	(474.1)	(711.2)	(948.3)	(1,185.4)
	Fuel Oil	4,750.1	5,214.7	(464.5)	-9.8%	210.4	(4.1)	(8.2)	(12.3)	(16.5)	(20.6)
	Regional Total SH-SC-WH					196,725.7	10,319.7	20,639.4	30,959.1	41,278.8	51,598.5
National Total of CO2 Emission Reduction [Million Metric Ton]							49.0	97.9	146.9	195.8	244.8
Percentage Savings							8.2%	16.3%	24.5%	32.7%	40.8%

3.8.3 Reductions in Summer Peak Electrical Demand

The national total reduction in summer peak electrical demand was calculated following the procedure described in section 3.6, and the results are listed in Table 10. As shown at the bottom of Table 10, **202 GW of summer peak electrical demand** could be avoided if the state-of-the-art GHP retrofits were deployed to all U.S. single-family homes. According to EIA (2008), the total U.S. net summer electric generating capacity as of December 31, 2008, was 1,010 GW. The 202-GW peak demand reduction from GHP retrofits could reduce the total required summer electric generating capacity in the United States by about 20%.

Table 10 National total of reduced summer peak electrical demand from GHP retrofit for existing US single-family homes

Census Region	SH-SC-WH System Types	Number of Single-Family Homes that Have Space Cooling	Percentage of Various Equipments Used for Space Cooling	Regional Average of Installed Space Cooling Capacity for the Reference Building	Normalized Peak Electrical Demand for Space Cooling of Existing SC Systems	Normalized Peak Electrical Demand for Space Cooling of the GHP System	Reduction in Normalized Peak Electrical Demand for Space Cooling from the GHP Retrofit	Percentage Reduction of Peak Electrical Demand for Space Cooling from GHP Retrofit	Estimated Regional Peak Electrical Demand for Space Cooling by Existing Systems	Estimated Regional Potential in Reduction of Peak Electrical Demand for Space Cooling				
										20% Market Penetration Rate for GHP Retrofit	40% Market Penetration Rate for GHP Retrofit	60% Market Penetration Rate for GHP Retrofit	80% Market Penetration Rate for GHP Retrofit	100% Market Penetration Rate for GHP Retrofit
		(millions)		Ton	kW/ton	kW/ton	kW/ton	%	GW	GW	GW	GW	GW	GW
Northeast	Space Cooling	11.1	100%	2.0	2.7	1.0	1.8	64.9%	60.7	7.9	15.8	23.6	31.5	39.4
	Central air conditioner	4.95	44.4%		2.3	1.0	1.4	59.0%						
	Room air conditioner	6.10	54.8%		3.0	1.0	2.1	68.5%						
	Both central and room AC	0.10	0.9%		2.7	1.0	1.7	64.4%						
Midwest	Space Cooling	18.6	100%	2.5	2.0	0.9	1.2	56.5%	95.3	10.8	21.5	32.3	43.0	53.8
	Central air conditioner	14.64	78.6%		1.9	0.9	1.0	53.8%						
	Room air conditioner	3.62	19.4%		2.5	0.9	1.6	64.5%						
	Both central and room AC	0.36	1.9%		2.2	0.9	1.3	59.8%						
South	Space Cooling	28.0	100%	3.0	2.0	1.0	1.0	52.2%	168.8	17.6	35.2	52.8	70.5	88.1
	Central air conditioner	22.71	81.0%		1.9	1.0	0.9	49.6%						
	Room air conditioner	4.64	16.5%		2.5	1.0	1.5	61.2%						
	Both central and room AC	0.70	2.5%		2.2	1.0	1.2	56.2%						
West	Space Cooling	9.5	100%	2.0	2.2	1.1	1.1	50.4%	41.4	4.2	8.3	12.5	16.7	20.8
	Central air conditioner	7.74	81.7%		2.1	1.1	1.0	47.8%						
	Room air conditioner	1.49	15.8%		2.7	1.1	1.6	59.9%						
	Both central and room AC	0.24	2.5%		2.4	1.1	1.3	54.6%						
National Total Reduction of Peak Electrical Demand for Space Cooling [GW]										40.4	80.8	121.3	161.7	202.1
Percentage Savings										11.0%	22.1%	33.1%	44.2%	55.2%

3.8.4 Savings in Consumer Energy Expenditures

By converting the delivered energy consumption data (both the calculated delivered energy consumption for SH-SC-WH in the reference building and the documented delivered energy consumption for all existing U.S. single-family homes) to the associated energy expenditures with the regional average utility rates for fuels and electricity listed in Table 11, the national potential savings in annual energy expenditures for SH-SC-WH was determined and is shown in Table 12. The regional average utility rates for fuels and electricity were obtained from the EIA Short-Term Energy Outlook (EIA STEO 2010).

Table 11. Utility rates for fuels and electricity in each Census Region.

Census Region	Gas		Oil		Propane		Electric	
	\$/Mcf		\$/gallon_O		\$/gallon_P		\$/MWh	
	Winter	Summer	Winter	Summer	Winter	Summer	Winter	Summer
Northeast	14.92	17.20	2.918	2.835	2.653	2.66	154.655	164.314
Midwest	10.93	13.54	2.826	2.796	1.909	1.84	97.984	105.770
South	14.67	18.77	2.866	2.734	2.429	2.33	105.899	110.320
West	10.31	11.30	2.978	2.968	2.354	2.23	109.361	118.881

As shown at the bottom of Table 12, \$53.4 billion of consumer energy expenditures, which accounts for 49.3% of all the energy expenditures associated with SH-SC-WH in existing U.S. single-family homes, could be saved each year by GHP retrofits at the 100% market penetration rate.

Unlike primary energy and CO₂ emissions, energy expenditures associated with water heating were reduced when existing water heaters were replaced with desuperheater-assisted electric water heaters, except for replacement of natural gas water heaters in the Northeast and West census regions. If the existing water heaters fired with fossil fuels were not replaced with desuperheater-assisted electric water heaters, the maximum savings of consumer energy expenditures from GHP retrofits would be reduced from 53.4 to **52.2 billion U.S. dollars**, which is **48.2%** of all the consumer energy expenditures for SH-SC-WH in existing U.S. single-family homes.

Table 12. National total of reduced energy expenditures from GHP retrofits for existing U.S. single-family homes.

Census Region	SH-SC-WH System Types	Regional Average Energy Expenditure by Existing SH-SC-WH System in Reference Building	Regional Average Energy Expenditure by GHP System in Reference Building	Regional Average Savings of Energy Expenditure in Reference Building	Percentage Savings of Energy Expenditure from GHP Retrofit	Regional Energy Expenditure for SH-SC-WH in All Single-Family Homes (RECS 2005)	Estimated Regional Potential in Savings of Energy Expenditure				
							20% Market Penetration Rate for GHP Retrofit	40% Market Penetration Rate for GHP Retrofit	60% Market Penetration Rate for GHP Retrofit	80% Market Penetration Rate for GHP Retrofit	100% Market Penetration Rate for GHP Retrofit
		\$	\$	\$	%	Million \$	Million \$	Million \$	Million \$	Million \$	Million \$
Northeast	Space Heating					18,834.3	2,186.7	4,373.3	6,560.0	8,746.6	10,933.3
	Electric Heat Pump	1878.8	651.1	1227.6	65.3%	84.7	11.1	22.1	33.2	44.3	55.4
	Electric Heater	2558.0	651.1	1906.8	74.5%	703.2	104.8	209.7	314.5	419.4	524.2
	Natural gas	1194.7	651.1	543.5	45.5%	7,896.5	718.5	1,437.0	2,155.5	2,874.1	3,592.6
	Propane/LPG	2240.7	651.1	1589.5	70.9%	769.8	109.2	218.4	327.7	436.9	546.1
	Fuel Oil	1929.8	651.1	1278.7	66.3%	9,380.0	1,243.0	2,486.0	3,729.0	4,972.1	6,215.1
	Space Cooling					2,686.4	407.2	814.3	1,221.5	1,628.7	2,035.8
	Central air conditioner	278.4	73.3	205.1	73.7%	1,716.4	252.9	505.8	758.7	1,011.6	1,264.5
	Room air conditioner	361.5	73.3	288.2	79.7%	894.1	142.6	285.1	427.7	570.3	712.8
	Both central and room AC	319.9	73.3	246.6	77.1%	75.9	11.7	23.4	35.1	46.8	58.5
	Water Heating					6,566.7	49.4	98.9	148.3	197.7	247.2
	Electric	778.7	484.2	294.5	37.8%	1,278.5	96.7	193.4	290.1	386.8	483.5
	Natural gas	406.0	484.2	-78.2	-19.3%	2,923.9	(112.6)	(225.2)	(337.8)	(450.4)	(563.0)
	Propane/LPG	733.9	484.2	249.7	34.0%	508.3	34.6	69.2	103.8	138.4	173.0
	Fuel Oil	527.9	484.2	43.7	8.3%	1,855.9	30.7	61.5	92.2	122.9	153.7
	Regional Total SH-SC-WH					28,087.4	2,643.3	5,286.5	7,929.8	10,573.0	13,216.3
Midwest	Space Heating					15,482.7	1,757.3	3,514.5	5,271.8	7,029.0	8,786.3
	Electric Heat Pump	1625.9	521.5	1104.5	67.9%	273.5	37.2	74.3	111.5	148.7	185.8
	Electric Heater	1926.6	521.5	1405.2	72.9%	1,107.5	161.6	323.1	484.7	646.2	807.8
	Natural gas	1029.5	521.5	508.1	49.3%	10,685.3	1,054.6	2,109.3	3,163.9	4,218.5	5,273.1
	Propane/LPG	1907.0	521.5	1385.6	72.7%	2,308.1	335.4	670.8	1,006.2	1,341.6	1,677.0
	Fuel Oil	2175.9	521.5	1654.5	76.0%	1,108.2	168.5	337.0	505.6	674.1	842.6
	Space Cooling					3,880.3	534.3	1,068.6	1,602.9	2,137.1	2,671.4
	Central air conditioner	255.9	81.7	174.2	68.1%	3,446.5	469.3	938.6	1,407.8	1,877.1	2,346.4
	Room air conditioner	332.3	81.7	250.7	75.4%	367.3	55.4	110.8	166.2	221.6	277.0
	Both central and room AC	294.1	81.7	212.4	72.2%	66.5	9.6	19.2	28.8	38.4	48.0
	Water Heating					6,794.4	252.5	505.0	757.4	1,009.9	1,262.4
	Electric	555.9	331.5	224.4	40.4%	1,807.7	145.9	291.8	437.8	583.7	729.6
	Natural gas	345.7	331.5	14.2	4.1%	4,137.7	34.0	68.0	102.0	136.0	170.0
	Propane/LPG	579.1	331.5	247.5	42.7%	826.7	70.7	141.4	212.0	282.7	353.4
	Fuel Oil	576.6	331.5	245.0	42.5%	22.3	1.9	3.8	5.7	7.6	9.5
	Regional Total SH-SC-WH					26,157.4	2,544.0	5,088.0	7,632.1	10,176.1	12,720.1
South	Space Heating					13,674.6	1,946.4	3,892.8	5,839.2	7,785.5	9,731.9
	Electric Heat Pump	636.9	240.9	396.0	62.2%	1,231.9	153.2	306.4	459.5	612.7	765.9
	Electric Heater	1049.9	240.9	809.0	77.1%	3,278.6	505.3	1,010.5	1,515.8	2,021.0	2,526.3
	Natural gas	690.0	240.9	449.1	65.1%	5,930.6	772.0	1,544.0	2,315.9	3,087.9	3,859.9
	Propane/LPG	1218.9	240.9	978.0	80.2%	2,417.1	387.9	775.8	1,163.6	1,551.5	1,939.4
	Fuel Oil	1118.1	240.9	877.2	78.5%	816.3	128.1	256.2	384.3	512.3	640.4
	Space Cooling					14,327.3	1,775.2	3,550.4	5,325.6	7,100.7	8,875.9
	Central air conditioner	476.3	185.8	290.4	61.0%	12,563.5	1,532.2	3,064.5	4,596.7	6,128.9	7,661.1
	Room air conditioner	618.5	185.8	432.7	70.0%	1,276.0	178.5	357.1	535.6	714.1	892.6
	Both central and room AC	547.4	185.8	361.5	66.0%	487.8	64.4	128.9	193.3	257.7	322.2
	Water Heating					11,396.0	797.2	1,594.3	2,391.5	3,188.6	3,985.8
	Electric	494.9	293.7	201.2	40.7%	5,271.8	428.6	857.2	1,285.9	1,714.5	2,143.1
	Natural gas	396.2	293.7	102.5	25.9%	5,105.4	264.2	528.4	792.6	1,056.9	1,321.1
	Propane/LPG	615.9	293.7	322.2	52.3%	933.2	97.6	195.3	292.9	390.5	488.2
	Fuel Oil	481.7	293.7	188.0	39.0%	85.6	6.7	13.4	20.1	26.7	33.4
	Regional Total SH-SC-WH					39,397.9	4,518.7	9,037.4	13,556.2	18,074.9	22,593.6
West	Space Heating					6,375.0	743.1	1,486.1	2,229.2	2,972.3	3,715.3
	Electric Heat Pump	664.6	264.3	400.3	60.2%	168.9	20.3	40.7	61.0	81.4	101.7
	Electric Heater	1088.7	264.3	824.3	75.7%	1,020.7	154.6	309.1	463.7	618.3	772.8
	Natural gas	493.0	264.3	228.6	46.4%	3,784.5	351.1	702.1	1,053.2	1,404.2	1,755.3
	Propane/LPG	1182.3	264.3	918.0	77.6%	915.7	142.2	284.4	426.6	568.8	711.0
	Fuel Oil	1157.8	264.3	893.4	77.2%	485.3	74.9	149.8	224.7	299.6	374.5
	Space Cooling					2,720.6	333.6	667.3	1,000.9	1,334.6	1,668.2
	Central air conditioner	283.3	111.0	172.4	60.8%	2,550.8	310.3	620.6	930.9	1,241.3	1,551.6
	Room air conditioner	368.0	111.0	257.0	69.8%	119.6	16.7	33.4	50.1	66.8	83.5
	Both central and room AC	325.7	111.0	214.7	65.9%	50.3	6.6	13.3	19.9	26.5	33.1
	Water Heating					5,651.1	(99.3)	(198.6)	(297.9)	(397.2)	(496.5)
	Electric	536.3	356.3	180.0	33.6%	1,314.1	88.2	176.4	264.6	352.8	441.0
	Natural gas	262.9	356.3	-93.5	-35.6%	3,549.2	(252.4)	(504.8)	(757.3)	(1,009.7)	(1,262.1)
	Propane/LPG	609.0	356.3	252.6	41.5%	764.5	63.4	126.8	190.3	253.7	317.1
	Fuel Oil	524.9	356.3	168.6	32.1%	23.3	1.5	3.0	4.5	6.0	7.5
	Regional Total SH-SC-WH					14,746.8	977.4	1,954.8	2,932.2	3,909.6	4,887.0
National Total of Energy Expenditure Savings [Billion \$]							10.7	21.4	32.1	42.7	53.4
Percentage Savings							9.9%	19.7%	29.6%	39.4%	49.3%

4. Valuing Investment in GHP Systems Compared to Alternatives

In this section, the GHP retrofit investment is valued in two different ways based on the predicted energy savings and installed cost premium of the GHP retrofit compared with alternative retrofit solutions. The first evaluation focuses on the net present value (NPV) over the life of the GHP retrofit investment, which is the difference between the installed cost premium of the GHP retrofit and the discounted present value of the saved energy costs over the life of the investment. The NPV is calculated with Equation 6:

$$NPV = \sum_{j=1}^m (E_j \cdot CEC_j) \times \sum_{i=1}^n \frac{(1+e)^{i-1}}{(1+d)^i} - CP \quad (\text{Eq. 6})$$

Where

j is the index number of various types of saved delivered energy, including electricity, natural gas, fuel oil, and propane/LPG;

E_j is the annual savings of energy type j ;

CEC_j is the current energy cost per unit of energy type j ;

i is the year;

e is the average annual escalation rate of energy prices;

d is the discount rate;

n is the service life of the GHP retrofit (i.e., the period of the calculation); and

CP is the cost premium of the GHP retrofit compared with alternative systems.

The second evaluation calculates the levelized cost of energy efficiency (**LCOEE**) of the GHP retrofit. **LCOEE** is analogous to the levelized cost of energy (LCOE), which is widely used in the utility industry to assess the investment of energy-generation systems, including all the costs over its lifetime: initial investment, operation and maintenance, and cost of capital. An NPV equation is written and solved to determine the value of LCOE such that the project's net present value is zero. This means that the LCOE is the minimum price at which energy must be sold for an energy project to break even. Similar to LCOE, LCOEE is the minimum price at which the **saved energy** must be valued for the investment in the GHP retrofit to break even. The calculation of **LCOEE** is expressed in Equation 7:

$$LCOEE = \frac{\sum_{i=1}^n \frac{I_i + M_i}{(1+d)^i}}{ES \cdot \sum_{i=1}^n \frac{(1+e)^{i-1}}{(1+d)^i}} \quad (\text{Eq. 7})$$

Where

I_i is the investment expenditure (including principal and interest) in year i ;

M_i is the operation and maintenance expenditures in year i ; and

ES is the annual energy savings achieved by the energy efficiency system (i.e., the GHP retrofit).

In the following sections, energy consumption and expenditures are presented for a few alternative retrofit solutions (section 4.1), the retrofit costs of the state-of-the-art GHP system and the alternatives are summarized (section 4.2), the financial parameters used in the evaluations are discussed (section 4.3), and finally the estimated NPV and **LCOEE** of the GHP retrofit at various discount rates are determined (sections 4.4 and 4.5).

4.1 Energy Consumption and Expenditures of Alternative Retrofit Solutions

Five alternative retrofit solutions are compared with the state-of-the-art GHP system. Brief descriptions of each alternative are provided in Table 13. All of these retrofit solutions are intended to reduce energy consumption and cost for space heating and cooling. However, unlike the conventional alternatives, the state-of-the-art GHP system also has an integral component called a desuperheater, which generates hot water very efficiently whenever the unit operates for heating or cooling. As discussed in section 3, the desuperheater usually works with an electric storage-type water heater, and the desuperheater-assisted electric water heater will reduce the primary energy consumption for water heating when replacing the existing electric water heater (without desuperheater). However, since the desuperheater-assisted electric water heater may consume more primary energy than conventional fossil-fuel fired water heater, it is assumed in this study that the existing conventional fossil-fuel fired water heaters are not replaced with the desuperheater-assisted electric water heater.

Table 13 List of alternative SH-SC systems for residential retrofit.

Name	Description	Note
Alt #1	SEER 13 AC and 80 AFUE natural gas furnace	Minimum allowed
Alt #2	SEER 21 AC and 93 AFUE natural gas furnace	State-of-the-art
Alt #3	SEER 13 ASHP with supplemental electrical heater	Minimum allowed
Alt #4	SEER 19 ASHP with supplemental electrical heater	State-of-the-art
Alt #5	SEER 19 ASHP with supplemental 93 AFUE natural gas furnace	State-of-the-art

As stated previously, source energy consumption accounts for all the primary energy consumed in generating and delivering energy to the building site. It thus is used as a metric to compare the various retrofit solutions. The national total annual source energy consumption for SH-SC-WH that would occur after retrofitting all existing U.S. single-family homes with each of the five alternative solutions is calculated using the same

procedure as described in section 3, and the results are listed in Table 14. Also shown in Table 14 is the national total source energy consumption of existing SH-SC-WH systems in all U.S. single-family homes, which is calculated from the delivered energy consumption data in RECS (2005). Based on these data and the total number of existing U.S. single-family homes with SH/SC-WH systems (79.3 million households), the average annual source energy savings per single-family home achieved from the GHP retrofit compared with the alternative solutions are calculated and listed in the last column of Table 14.

Table 14. Source energy savings from GHP retrofits vs. alternatives.

System Type	National Total Annual Source Energy Consumption for SH-SC-WH in U.S. Single-family Homes	National Total Annual Source Energy Savings (Compared with Existing Systems)	National Average of Annual Source Energy Savings per Single-Family Home (Compared with Existing Systems)	National Average of Annual Source Energy Savings per Single-Family Home from GHP Retrofit (Compared with Alternatives)
	Quad BTU	Quad BTU	MBTU	MBTU
Existing SH-SC-WH Systems	9.3			
State-of-the-art GHP System	5.1	4.2	53.0	
Alt #1	8.3	1.0	12.6	40.4
Alt #2	7.3	2.0	25.2	27.7
Alt #3	10.2	-0.9	-11.3	64.3
Alt #4	10	-0.7	-8.8	61.8
Alt #5	7.3	2.0	25.2	27.7

As shown in Table 14, retrofitting the existing SH-SC systems with Alt #3 and Alt #4, which use ASHPs and auxiliary electric resistance heaters, actually increases the annual source energy consumption due to increased use of electricity at an efficiency level too low to offset the high source energy conversion factor (3.365) for electricity. This result indicates that retrofitting existing SH-SC systems with Alt #3 and Alt #4 may not be a good strategy for reducing source energy consumption and greenhouse gas emissions, especially when the electricity is generated with fossil fuels and the auxiliary electric resistance heater has to run frequently to supplement the ASHP⁵. The table also shows that Alt #5 (19 SEER ASHP supplemented with 93 AFUE gas furnace) consumes almost the same amount of source energy as Alt #2 does, which is a combination of SEER 21 AC and 93 AFUE gas furnace. As a result, in the following economic analysis, only Alt #1 and Alt #2 are included.

The national total annual savings in energy expenditures resulting from the GHP retrofit versus the two alternatives (Alt #1 and Alt #2) are summarized in Table 15. In the same table, the average annual energy expenditures for the state-of-the-art GHP system and the two alternatives per single-family home are also presented. The last column of the table shows the average savings per home in annual energy expenditures from the GHP retrofit versus the two alternatives. On average, retrofitting the existing SH-SC systems with the state-of-the-art GHP system saves \$469 and \$332 each year compared with Alt #1 and Alt #2, respectively.

⁵ The heating capacity and efficiency of ASHPs degrade significantly at low ambient temperatures, and the “defrosting operation” often results in uncomfortable “cold air blow” inside the building. It is thus common that electric resistance heat will kick in to override the heat pump when the ambient temperature is below 35°F.

Table 15. Annual savings in energy expenditures resulting from GHP retrofits vs. alternatives.

System Type	National Total Annual Energy Expenditure for SH-SC-WH in U.S. Single-family Homes	National Total Annual Energy Expenditure Savings (Compared with Existing Systems)	National Average of Annual Energy Expenditure for SH-SC-WH per Single-family Home	National Average of Annual Energy Expenditure Savings per Single-Family Home from Various Retrofits (Compared with Alternative Systems)
	Billion \$	Billion \$	\$	\$
Existing SH-SC-WH Systems	108.4		1367.0	
State-of-the-art GHP System	56.2	52.2	708.7	
Alt #1	93.4	15.0	1177.8	469.1
Alt #2	82.5	25.9	1040.4	331.7

Figure 5 shows annual savings in electricity and natural gas from the GHP retrofit compared with Alt #1 and Alt #2 in each of the four census regions. As shown in Figure 5, the GHP retrofit significantly reduces the consumption of natural gas (due to displacement of the natural gas furnaces), but it slightly increases the electricity consumption in all the census regions except in the south, where savings in electricity for space cooling and water heating (only in homes with existing electric water heaters) more than offsets the electricity consumed by the GHP units for space heating.




Fig. 5. Saved electricity and natural gas from GHP retrofits vs. alternatives in each census region.

4.2 Retrofit Cost of the GHP System and Alternatives

Only a few published papers and reports were found that documented the installed cost of GHP systems. Kavanaugh (1995) reported that the average cost of a 3-ton GHP system with vertical ground heat exchanger was \$8,997. The average cost of the vertical ground heat exchanger was \$1,028 per installed cooling ton. These average costs were in 1995 U.S. dollars and obtained from a national survey of the cost of purchasing and installing GHP systems. The average cost of each major component of the GHP system and an analysis of the potential for cost reduction were presented in the report and are summarized in Table 16.

Table 16. Components of GHP system cost and estimated potential cost reductions.

Itemized Cost	3-Ton GHP System Installed Cost (Kavanaugh 1995)		3-Ton GHP System Cost Reduction Potential (Kavanaugh 1995)	
	1995 \$	2010 \$	1995 \$	2010 \$
Ground loop	\$3,077	\$4,330	\$360	\$507
Heat pump (including loop pump)	\$2,717	\$3,823	\$1,160	\$1,632
Indoor installation	\$1,898	\$2,671	\$540	\$760
Ductwork	\$1,305	\$1,836	\$0	\$0
Total Installed Cost	\$8,997	\$12,661		

A recent report (DOD 2007) indicates that the average cost of GHP systems installed in residences of Department of Defense Facilities is \$4,600 in 2006 dollars for each cooling ton of capacity or \$13,800 for a 3-ton system. This cost is higher than that reported in the table above but includes the extra costs associated with projects at DOD facilities (Davis Beacon wages, secure facility access costs, training costs, transactions costs for multiple levels of oversight, etc.). When these factors are considered, the DOD experience appears comparable to the table above.

As described in the Buildings Energy Data Book (DOE-EIA 2009), the typical size of U.S. single-family homes is 1,900 ft². Given the floor space, insulation, and air-tightness characteristics typical of the existing housing stock, a 3-ton GHP system is assumed in this study to be the average for U.S. single-family homes.

In this study, except for the cost of the state-of-the-art GHP unit, all other cost components of the 3-ton GHP system with vertical ground heat exchanger are adopted from Kavanaugh (1995), with correction for 2.47% annual inflation between 1995 and 2010. The cost of the state-of-the-art GHP unit (with desuperheater), central air conditioners, and gas furnaces are the typical list prices available in the current market. The costs of indoor installation and adaptation to existing ductwork are assumed to be

identical for the GHP system and the alternatives, so they were not included in the calculation of the cost premium for the GHP retrofit.

The total retrofit and comparable costs of the 3-ton state-of-the-art GHP system and the two alternative systems are presented in 2010 dollars in Table 17. As shown in the table, the national average cost of retrofitting existing SH-SC systems with the 3-ton state-of-the-art GHP system is more than double the cost (\$11,241 vs. \$4,500) of Alt #1 — a new, minimum-code-compliant, conventional SH-SC system. However, if the estimated cost reduction potential (Kavanaugh 1995) is fully realized, the cost of the GHP retrofit will be reduced by 19%, to \$9,102. Though it is still about double the cost for Alt #1, it is very close to the cost of Alt #2 — the state-of-the-art conventional SH-SC system (\$9,102 vs. \$8,642).

Table 17. Costs of the state-of-the-art GHP system and alternative systems.

System	Itemized Cost	Average Market Price	Reduced Price
State-of-the-Art GHP System	Ground loop	\$4,330	\$3,823
	Heat pump (include pump)	\$6,911	\$5,279
	Indoor installation	\$2,671	\$1,911
	Ductwork	\$1,836	\$1,836
	Total Installed Retrofit Cost	\$15,748	\$12,849
	Comparable Cost (without indoor installation and ductwork)	\$11,241	\$9,102
Alternatives	Itemized Cost	Alternative #1	Alternative #2
		SEER 13 AC and 80 AFUE gas furnace	SEER 21 AC and 93 AFUE gas furnace
	AC unit	\$2,500	\$5,142
	Gas furnace	\$2,000	\$3,500
	Indoor installation	\$2,671	\$2,671
	Ductwork	\$1,836	\$1,836
	Total Installed Retrofit Cost	\$9,007	\$13,149
	Comparable Cost (without indoor installation and ductwork)	\$4,500	\$8,642

4.3 Variables and Parameters Used in the Calculations

In this study, we assume that the homeowner pays for the retrofit with cash at the beginning of year one so that there is no interest cost. It is also assumed that the life of the investment is 20 years, which is the typical service life of the GHP unit. Although the ground heat exchanger would typically remain in service for a much longer time period than the GHP unit, this simplified analysis does not address this value. And although the maintenance cost of a GHP system is typically lower than that of conventional systems, it is also not accounted for in this study. As a result, calculations for NPV and LCOEE of the GHP retrofit are simplified to only include four variables — cost premium of the 3-

ton GHP retrofit (obtained from Table 17), annual savings in energy consumption or energy expenditures from the GHP retrofit, average annual energy escalation rate, and discount rate over the life of the investment. The predicted annual savings in energy expenditures per single-family home listed in Table 15 are used to calculate the NPV of the GHP retrofit. The predicted savings in delivered energy include both natural gas and electricity. To calculate LCOEE of the GHP retrofit, the avoided natural gas consumption is converted to “indirect electricity savings” as described in section 4.5 and the total (direct and indirect) electricity savings from the GHP retrofit compared with the alternatives is listed in Table 19.

The two key financial parameters, average annual energy escalation rate and discount rate over the life of the investment, are discussed in the following paragraphs.

Energy Escalation Rate

The average annual energy escalation rate for 2010 through 2030 was determined with the Energy Escalation Rate Calculator developed for the DOE’s Federal Energy Management Program (FEMP 2010). This tool calculates the average rate (across all energy forms) of energy price escalation over the duration of the analysis period, weighted by the proportions of each energy type saved by the project. Since, as shown in Figure 5, most energy savings from the GHP retrofit comes from avoided natural gas consumption, the calculated average escalation rate is appropriately weighted toward the escalation rate of natural gas price over the 20-year period, which is 5.14% based on the 3.4% inflation rate.

Discount Rate

The 2010 real discount rate for public investment and regulatory analysis is 7%. However, historical data show that the discount rate has varied widely in past years from 0.5% to 14% (Federal Reserve Bank of New York 2010). As a result, instead of assuming a particular discount rate, a series of discount rates ranging from 0 to 15% with an interval of 3% are used in the calculations for the NPV and LCOEE of the GHP retrofit.

4.4 Predicted NPV from Investment in GHP Retrofits

NPV of GHP retrofits in four scenarios are calculated with various discount rates using Equation 6. The four scenarios are:

- State-of-the-Art GHP system vs. Alt #1
- State-of-the-Art GHP system (with reduced cost) vs. Alt #1
- State-of-the-Art GHP system vs. Alt #2
- State-of-the-Art GHP system (with reduced cost) vs. Alt #2

The predicted national average NPV gained from retrofitting a typical existing single-family home with the state-of-the-art GHP system in the above four scenarios and with various discount rates are listed in Table 18. As indicated in Equation 6, a positive value of the calculated NPV means the discounted present values of the saved future energy costs exceed the cost premium of the GHP retrofit. Correspondingly, a negative for NPV means the cost premium is not offset by future energy cost savings. The calculated NPV is also presented in Figure 6 to illustrate its relationship with the discount rate.

As a sanity check, the simple payback periods⁶ of the investments are also calculated and summarized in Table 18. As shown in the table, compared with Alt #1, the national average simple payback period for the GHP retrofit at current market prices is 14.4 years and falls to 9.8 years if the 19% cost reduction potential suggested by Kavanaugh (1995) is fully realized. Considering the higher cost of the state-of-the-art GHP units, these results are in line with the 8.6- to 12-year simple payback periods indicated in the DoD (2007) report. The simple payback period for the GHP retrofit becomes much shorter when compared with the state-of-the-art conventional system (Alt #2). With the 19% cost reduction, the simple payback period of the GHP retrofit is only 2.4 years.

Data in Table 18 and Figure 6 show that the NPV of the GHP retrofit is higher when compared with the state-of-the-art conventional system (Alt #2) than with the minimum-code-compliant conventional system (Alt #1). This result is not surprising since the cost premium of the GHP retrofit is much lower versus Alt #2, especially when the 19% cost reduction potential of the GHP system is fully realized. When compared with Alt #2, investments in the GHP retrofit at current market prices show a positive NPV over the 20-year life even when future energy cost savings are discounted at rates as high as 14%. However, when compared with Alt #1, investment in the GHP retrofit at current market prices will only yield a positive NPV when the discount rate is lower than 8%. If the 19% cost reduction potential of GHP systems can be fully realized, investments in the GHP retrofit generally have positive NPVs even with high discount rates, especially when compared with the state-of-the-art conventional system (Alt #2). This result implies that with currently enacted federal tax credits, which offset 30% of the installed cost of GHP systems (valid through 2016), investments in GHP retrofits are currently quite attractive across the board, presuming homeowners are earning income and paying taxes.

Table 18. Simple payback period and NPV for GHP retrofits at various discount rates.

Profit of GHP Retrofit	Simple Payback Period Year	Discount Rate					
		0%	3%	6%	9%	12%	15%
State-of-the-Art GHP System vs. Alt #1	14.4	\$ 9,002	\$ 4,411	\$ 1,460	\$ (497)	\$ (1,834)	\$ (2,775)
State-of-the-Art GHP System (with Reduced Cost) vs. Alt #1	9.8	\$ 11,141	\$ 6,550	\$ 3,599	\$ 1,642	\$ 305	\$ (636)
State-of-the-Art GHP System vs. Alt #2	8.9	\$ 8,189	\$ 4,943	\$ 2,857	\$ 1,474	\$ 528	\$ (137)
State-of-the-Art GHP System (with Reduced Cost) vs. Alt #2	2.4	\$ 10,328	\$ 7,082	\$ 4,996	\$ 3,612	\$ 2,667	\$ 2,002

⁶ Simple payback is calculated by dividing the cost premium of the GHP retrofit by the energy expenditure savings in the first year, with neither energy cost escalation nor discount rate accounted for.




Fig. 6. Calculated profits of 3-ton GHP retrofit at various discount rates.

4.5 Predicted Levelized Cost of Energy Efficiency of GHP Retrofits

Typically, levelized costs are calculated based on the savings of one type of energy, such as electricity. However, as shown in Figure 5, while the GHP retrofit reduces natural gas consumption, it also increases or decreases the consumption of electricity. To account for these two types of energy in the LCOEE calculation, the avoided natural gas consumption is converted to “indirect electricity savings,” which is the electricity that can be generated and delivered to a residence using the avoided natural gas consumption at the residence. Therefore the total saved energy used in the LCOEE calculation is the sum of the indirect electricity savings (representing savings in natural gas) and the direct savings (positive or negative) of delivered electricity at the residence. The typical thermal efficiency of combined-cycle natural gas power plants (50%)⁷ and the national average of transmission and distribution losses of electricity (9.9%) (NREL 2007) are used to calculate the indirect electricity savings. The estimated total (direct and indirect) electricity savings from the GHP retrofit compared with Alt #1 and Alt #2 are listed in Table 19.

⁷ From http://www.naturalgas.org/overview/uses_electrical.asp.

Table 19. Total (direct and indirect) electricity savings from the GHP retrofit compared with Alt #1 and Alt #2.

Base Case	National Total (Direct and Indirect) Electricity Savings from GHP Retrofit	National Average of Annual (Direct and Indirect) Electricity Savings per Single-Family Home from GHP Retrofit
	Trillion W-Hr	kWh
Alt #1	432.0	5447.7
Alt #2	340.0	4287.5

The LCOEE of the GHP retrofit in the four scenarios described in section 4.4 and at various discount rates are calculated using Equation 7, and the results are listed in Table 20. Similar to LCOE (for energy generation systems), which is the minimum price at which the **generated energy** must be sold for an energy project to break even, LCOEE is the minimum price at which the **saved energy** must be valued for the investment in GHP retrofits to break even. As shown in Table 20, the LCOEE of the GHP retrofit is always less than the annual average residential electricity price in 2010 (11.5 cents per kWh)⁸ when compared with Alt #2. When compared with Alt #1, the state-of-the-art GHP at current market prices is better than break-even up to a discount rate of 7%, and with the previously discussed 19% cost reduction, is better than break-even up to a discount rate of 12%.

Table 20. LCOEE of GHP retrofit in four scenarios and at various discount rates.

LCOEE (Cents per kWh)	Discount Rate					
	0%	3%	6%	9%	12%	15%
State-of-the-Art GHP System vs. Alt #1	6.2	8.3	10.8	13.6	16.6	19.8
State-of-the-Art GHP System (with Reduced Cost) vs. Alt #1	4.2	5.7	7.4	9.3	11.3	13.5
State-of-the-Art GHP System vs. Alt #2	3.0	4.1	5.3	6.6	8.1	9.7
State-of-the-Art GHP System (with Reduced Cost) vs. Alt #2	0.5	0.7	0.9	1.2	1.4	1.7

4.6 Uncounted Values and Benefits

Due to the lack of established valuing mechanisms and insufficient resources to develop the methods, the calculations for NPV and LCOEE for the GHP retrofit in this analysis do not account for several benefits achieved from the GHP retrofits, including reduction

⁸ EIA Short-Term Energy and Summer Fuels Outlook (April 6, 2010). Available at http://www.eia.doe.gov/steo#Electricity_Markets

of CO₂ emissions and summer peak electrical demand. In addition, the residual value of the vertical ground loop heat exchanger, which has a service life far longer than 20 years, was not accounted for. These unincluded benefits are believed to be substantial.

As shown in Table 21, compared with Alt #1 (SEER 13 AC), the state-of-the-art GHP system reduces summer peak electrical demand by 0.5 – 1 kW per cooling ton depending on where the building is located. However, the reduction of summer peak electrical demand is less than 0.3 kW/ton when the GHP system is compared with Alt #2 (SEER 21 AC). When deployed on a large scale, the GHP retrofit could defer or avoid the need for significant amounts of new electricity generation capacity. According to a recent report (Lazard 2008), the capital cost of a new combined-cycle natural gas power plant is \$900 – \$1,100 per kW, and the cost is 3 – 5 times higher if the electricity is generated with renewable energy or in de-carbonized fossil-fuel power plants. Obviously, if the summer peak electrical demand reduction from GHP retrofits is valued more highly by including the avoided capital cost of new electricity generation capacity, the cost premium of the GHP retrofit would be significantly reduced.

Table 21. Peak electrical demand for cooling in four U.S. census regions.

System	Peak Electrical Demand for Cooling [kW/ton]			
	Northeast	Midwest	South	West
State-of-the-Art GHP	0.96	0.96	0.98	1.09
Alt #1	1.95	1.89	1.55	1.76
Alt #2	1.23	1.16	1.20	1.27

Table 22 compares the CO₂ emissions of the state-of-the-art GHP system with those of Alt #1 and Alt #2 in the four U.S. census regions. Data in Table 22 indicate that the state-of-the-art GHP system can reduce CO₂ emissions by an average of 2.5 and 1.6 metric tons per U.S. single-family home compared with Alt #1 and Alt #2, respectively.

Table 22. CO₂ reduction potential of GHP retrofits compared with alternatives.

System Type	National Total Annual CO ₂ Emissions for SH-SC-WH in U.S. Single-family Homes	National Total Annual CO ₂ Emissions Reduction (Compared with Existing Systems)	National Average of Annual CO ₂ Emissions Reduction per Single-Family Home (Compared with Existing Systems)	National Average of Annual CO ₂ Emissions Reduction per Single-Family Home from GHP Retrofit (Compared with Alternatives)
	Million Metric Ton	Million Metric Ton	Metric Ton	Metric Ton
Existing SH-SC-WH Systems	599.7			
State-of-the-art GHP System	328	271.7	3.4	
Alt #1	522.9	76.8	1.0	2.5
Alt #2	458.7	141.0	1.8	1.6

If the residual value of the ground heat exchangers and the reductions in summer peak electrical demand and CO₂ emissions can be fairly valued in the economic analysis, GHP retrofits will appear more favorable using the NPV and LCOEE metrics.

5. Conclusions

This report assesses the potential of national benefits from retrofitting U.S. single-family homes with state-of-the-art GHP systems at various penetration rates. The assessment is conducted using energy consumption data for SH-SC-WH in existing U.S. single-family homes obtained from the Residential Energy Consumption Survey (RECS 2005) and relative differences in annual energy consumption between the state-of-the-art GHP system and existing residential SH-SC-WH systems. The impacts of various climate and geological conditions, as well as efficiency and market share of existing residential SH-SC-WH systems, have been taken into account in the assessment.

The analysis shows that replacing all SH-SC-WH systems in existing U.S. single-family homes with properly designed, installed, and operated state-of-the-art GHP systems would yield significant benefits each year, including savings of 4.2 quad Btu primary energy, reduction of 271.7 million metric tons of CO₂ emissions, savings of \$52.2 billion in energy expenditures, and reduction of 202.1 gigawatt in summer peak electrical demand. The analysis also shows that the benefits of GHP retrofits are significant even at lower market penetration rates.

An economical analysis shows that, compared with conventional residential space heating and cooling systems, investments in retrofitting existing single-family homes with the state-of-the-art GHP system will yield a positive NPV over a 20-year period at current market prices and without any financial incentives when the discount rate is lower than 8%. The levelized cost analysis shows that saving energy with the GHP retrofit is cheaper than generating and delivering electricity to residences when the discount rate is lower than 8%. With the enacted federal tax credits for 30% of the installed cost of a GHP system (valid through 2016), investments in the state-of-the-art GHP system could be profitable even at higher discount rates. The GHP retrofit investment would be more favorable should the residual value of the ground loop heat exchanger and the value of reduced CO₂ emissions and summer peak electrical demand be accounted for.

6. References

American Physical Society, 2008. How America can look within to achieve energy security and reduce global warming. <http://www.aps.org/energyefficiencyreport/>

Ellis, D., 2008. Field Experience with Ground-Source Heat Pumps in Affordable Low Energy Housing. Proceedings of the 9th IEA Heat Pump Conference, 20-22 May 2008, Zurich, Switzerland.

DoD Office of the Deputy Under Secretary of Defense—Installations and Environment, January 2007. Report to Congress: Ground-Source Heat Pumps at Department of Defense Facilities.

DOE BTP, 2005. Guide for Evaluation of Energy Savings Potential.

DOE-EIA, 2009. 2009 Buildings Energy Data Book. <http://buildingsdatabook.eren.doe.gov/>.

- DSIRE (Database of State Incentives for Renewables and Efficiency), 2010.
<http://www.dsireusa.org/>
- EPA (U.S. Environmental Protection Agency), 1993. Space Conditioning: the Next Frontier. April.
- IPCC, 2007. Mitigation of climate change. Chapter 6, Residential and commercial buildings.
www.ipcc.ch/ipccreports/ar4-wg3.htm .
- Executive Office of the President's National Science and Technology Council, 2008. Federal R&D agenda for net-zero energy, high-performance green buildings.
<http://ostp.gov/galleries/NSTC%20Reports/FederalRDAgendaforNetZeroEnergyHighPerformanceGreenBuildings.pdf>
- EIA, 1978-1997. Trends in Residential Air-Conditioning Usage from 1978 to 1997.
http://www.eia.doe.gov/emeu/consumptionbriefs/recs/actrends/recs_ac_trends.html
- EIA, 2008. Electric Power Industry 2008: Year in Review.
http://www.eia.doe.gov/cneaf/electricity/epa/epa_sum.html .
- Federal Reserve Bank of New York, 2010. Historical Changes of the Federal Funds and Discount Rate. Available at <http://www.newyorkfed.org/markets/statistics/dlyrates/fedrate.html> .
- GHPC, 1994. National earth comfort program: summary edition. Geothermal Heat Pump Consortium, Inc.
- Hackel, S., G. Nellis, and S. Klein, 2009. Optimization of cooling dominated hybrid ground-coupled heat pump systems. ASHRAE Transactions 109 (1).
- Hughes, P.J., and L. Pratsch, 2002. Technical and Market Results of Major U.S. Geothermal Heat Pump Programs, in proceedings of the 7th IEA Heat Pump Conference, vol. 1, pp. 325-342, Beijing, China, May 2002.
- Hughes, P., 2008. Geothermal (Ground-Source) Heat Pumps: Market Status, Barriers to Adoption, and Actions to Overcome Barriers, ORNL/TM-2008/232.
- Kavanaugh, S., 1995. Cost Containment for Ground-Source Heat Pumps, Final Report.
- Lazard, 2008. Levelized Cost of Energy Analysis – Version 2.0. Available at [http://www.narucmeetings.org/Presentations/2008%20EMP%20Levelized%20Cost%20of%20Energy%20-%20Master%20June%202008%20\(2\).pdf](http://www.narucmeetings.org/Presentations/2008%20EMP%20Levelized%20Cost%20of%20Energy%20-%20Master%20June%202008%20(2).pdf)
- Liu, X., 2008. Enhanced Design and Energy Analysis Tool for Geothermal Water Loop Heat Pump Systems. Proceedings of the 9th IEA Heat Pump Conference, 20-22 May 2008, Zurich, Switzerland.
- NREL, 2007. Source Energy and Emission Factors for Energy Use in Buildings. National Renewable Energy Laboratory Technical Report NREL/TP-550-38617.

RECS, 2005. Public Use Microdata Files.

<http://www.eia.doe.gov/emeu/recs/recspubuse05/pubuse05.html>.

Rybach, L., 2005. The advance of geothermal heat pumps – worldwide. IEA Heat Pump Center News Letter, 23(4).

UNEP (United Nations Environmental Programme), 2007. Buildings and climate change: Status, challenges and opportunities. www.unep-sbci.org/Ressources/ReportsStudies/

Appendix A – Description of Reference Single-family Home

The selected reference single-family home, a one-story, slab-on-grade, wood-frame house, is depicted in Figure A-1. Its key characteristics are listed in Table A-1.




Fig. A-1. Illustration of the selected reference single-family home.

Table A-1. Key characteristics of the selected reference single-family house

Main entrance orientation	North
Conditioned floor area	1618 sf
Construction	Wood frame
Story	One
Ceiling insulation	R-38 blown cellulose at ceiling
Walls insulation	R-19 blown cellulose + R-3 insulating sheathing
Foundation insulation	Slab on grade, R-4 perimeter insulation
Windows	Double-glazed; U = 0.5, SHGC = 0.57; Mostly south-facing with overhang
Infiltration rate	0.19 ACH
Lighting	90% compact fluorescent lighting
Appliances and miscellaneous	ENERGY STAR refrigerator, clothes washer, dishwasher, TV, computer
Air-handler location	In conditioned space (utility room)
Ducts	In vented attic, R-6 insulation, 5% or less leakage to the outside

Appendix B – Description of GeoDesigner Software

GeoDesigner estimates annual energy consumption and expenditures for space heating, space cooling, and water heating (SH-SC-WH) in single-family homes that use geothermal heat pump (GHP) system or other typical residential SH-SC-WH systems.

GeoDesigner utilizes the ASHRAE modified bin analysis method to calculate space heating and cooling loads (the amount of heat needs to be removed from or added into the space to maintain a certain temperature set point) of a single-family home at various outdoor dry-bulb temperatures, which are sorted into discrete groups (bins) with the number of hours of occurrence of each temperature bin. The calculation is based on user-specified peak heat loss and heat gain from building envelop at design conditions (the highest and lowest outdoor dry-bulb temperature), and approximations for miscellaneous electric load, solar heat gain, occupancy level, and the construction quality (air tightness of the building). GeoDesigner has a library of the bin weather data for most major cities in the United States as well as the design outdoor dry-bulb temperature (adopted from handbook of American Society of Heating Refrigeration and Air-Conditioning Engineers [ASHRAE]), the deep earth temperature, surface soil temperature swing and delay (adopted from the design and installation manual of International Ground Source Heat Pump Association [IGSHPA]) at each of the locations.

GeoDesigner calculates domestic hot water load of a single-family home based on average city water supply temperature where the building is located, user-specified hot water supply temperature, and the number of occupants in the building. The calculated domestic hot water load is constant over all temperature bins.

GeoDesigner has a library of performance data for GHP units and conventional SH-SC-WH equipments, including air source heat pump units, air conditioners, furnaces/boilers, and water heaters. The library covers a wide range of equipments with efficiencies varied from less than current code allowed minimum to the highest available from the state-of-the-art equipments, and fuel types of furnace/boiler and water heater includes electricity, natural gas, heating oil, and propane/LPG.

GeoDesigner allows user to select ground heat exchangers from a large collection including vertical bores, horizontal loops, pond loop, and well water. It offers two options for the design of selected ground heat exchangers: auto-sized by itself or user-specified. The sizing algorithms implemented in GeoDesigner for various types of ground heat exchangers are adopted from the design and installation manual of IGSHPA.

To simulate the annual energy consumption of a GHP system, GeoDesigner calculates the ground heat exchanger leaving fluid temperature (LFT), which is the entering fluid temperature (EFT) of the heat pump unit, based on the design of the selected ground heat exchanger and the space heating/cooling loads at each temperature bin. With these calculated EFT and the performance curves of the user-selected heat pump unit (obtained from manufacturer's catalog data), which correlate the heat pump capacity and efficiency to the EFT, GeoDesigner calculates power consumption of the GHP system for providing

space heating/cooling loads at each temperature bin and over the entire year. The heat pump efficiency accounts for all the power consumptions from the heat pump compressor, fan, and circulation pump⁹. The efficiency degradation due to the cycling loss of the heat pump at part load conditions is also taken into account in the calculation with a part-load performance curve for the selected heat pump. When the de-super-heater option is selected, GeoDesigner calculates the contribution of the de-super-heater for water heating and the associated power consumption.

Similarly, the annual energy consumption of air source heat pump (ASHP) or air conditioner (AC) is determined based on the space heating/cooling loads and the outdoor dry-bulb temperature at each temperature bin as well as the performance curves of the user-selected ASHP/AC unit (obtained from manufacturer's catalog data), which correlate the ASHP/AC capacity and efficiency to the outdoor dry-bulb temperature. The Auxiliary heating, either supplementing or overriding the ASHP, is accounted for in the energy calculation for ASHP system.

The energy consumption of furnace/boiler and water heater (non-heat pump type) is calculated straight forwardly with the total space heating and water heating loads and the efficiencies of the selected furnace/boiler and water heater. Electric consumptions associated with the fossil fuel fired furnace/boiler and water heater are included in the energy calculation.

With decades of continued development, GeoDesigner becomes very user-friendly and robust in performing energy analysis for residential SH-SC-WH systems. It has been widely used in the design and energy analysis for residential GHP applications. A recent report shows that the energy consumption predicted by GeoDesigner matches the metered data fairly well (Ellis 2008).

GeoDesigner still has some limitations. First, compared with more sophisticated hourly energy simulation, the bin analysis utilized by GeoDesigner is relatively less accurate in estimating the impacts of other weather elements (i.e. solar, wind, precipitation, and etc.) and the heat gain from activities inside the building (i.e. lighting, cooking, showering, and etc.) on the building heating/cooling loads. The bin analysis also limits the capability for more detailed analysis of electrical demand of the building. Second, the algorithm used by GeoDesigner for calculating the ground heat exchanger LFT does not account for the loading history of the ground and, as a result, it may underestimate the LFT at some temperature bins, especially those most likely occurring at the end of a heating/cooling season.

Comparison results with other more sophisticated hourly energy analysis programs show that, while there are some discrepancies in the predicted total energy consumption of a particular SH-SC-WH system between GeoDesigner and the more sophisticated

⁹ The fan power is adopted from manufacturers' catalog data for 0.5 External Static Pressure and the pumping power is estimated for typical total length/depth of the loop/ well plus head loss in heat pump (condenser) and assuming typical pump efficiencies.

programs, the relative difference in energy consumption between different SH-SC-WH systems predicted by GeoDesigner and the more sophisticated programs are fairly close.

Appendix C – Population-Weighted Average of Energy Consumptions, CO₂ Emissions, and Energy Expenditures of each Typical SH-SC-WH System in each Census Region

C-1 Northeast Region

Delivered Energy

Cen Region	Cim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
		State	City	County			Heat	Cool	HW	Heat	Cool	HW	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW
							MWh	MWh	MWh	MWh	MWh	MWh	MWh	MWh	MWh	MWh	Mcf	MWh	MWh	MWh	MWh	MWh	MWh	MWh	MWh	MWh	MWh
Northeast	4A	PA	Philadelphia	Philadelphia	21,879,116	48.1%	3.6	8.8	3.3	10.0	2.4	5.2	14.3	2.5	5.2	0.5	64.1	2.5	27.0	0.5	700.8	2.5	295.1	0.7	537.5	2.5	195.9
Northeast	5A	MA	Boston	Suffolk	28,102,970	51.6%	4.2	0.4	3.6	12.1	1.3	5.6	16.6	1.6	5.6	0.6	74.6	1.6	28.8	0.6	915.6	1.6	314.7	0.7	625.6	1.6	209.0
Northeast	6A	ME	Bangor	Penobscot	4,515,671	8.3%	7.2	0.2	3.5	22.8	0.9	5.9	26.9	0.9	5.9	0.9	129.9	0.9	30.5	0.9	1,321.9	0.9	333.3	1.1	1,013.9	0.9	221.4
Total Pop Wgt Avg Arithmetic Average					54,497,757	100%	4.2	0.5	3.5	12.1	1.8	5.5	16.5	1.9	5.5	0.6	74.2	1.9	28.2	0.6	811.5	1.9	308.4	0.7	622.4	1.9	204.8
							5.7	0.3	3.6	17.5	1.2	5.7	21.8	1.3	5.7	0.7	97.8	1.3	29.7	0.7	1,069	1.3	324	0.9	620	1.3	215

Utility Cost

Cen Region	Cim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
		State	City	County			Heat	Cool	HW	Heat	Cool	HW	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW
							\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$	\$
Northeast	4A	PA	Philadelphia	Philadelphia	21,879,116	48.1%	550.1	130.1	520.2	1,550.4	395.0	832.5	2,209.2	412.6	832.5	80.4	956.1	412.6	433.5	80.4	1,859.5	412.6	783.6	104.4	1,568.4	412.6	563.6
Northeast	5A	MA	Boston	Suffolk	28,102,970	51.6%	656.5	63.8	578.5	1,869.2	254.5	888.0	2,571.1	265.9	888.0	85.5	1,112.7	265.9	462.4	85.5	2,164.1	265.9	835.8	111.0	1,825.4	265.9	601.2
Northeast	6A	ME	Bangor	Penobscot	4,515,671	8.3%	1,117.1	35.7	562.8	3,529.7	148.4	937.9	4,166.8	154.9	937.9	136.5	1,893.3	154.9	469.7	136.5	3,597.3	154.9	865.3	175.9	2,958.3	154.9	636.7
Total Pop Wgt Avg Arithmetic Average					54,497,757	100%	652.0	88.1	553.8	1,878.8	302.1	869.9	2,558.0	315.6	869.9	87.6	1,107.1	315.6	453.1	87.6	2,153.1	315.6	818.9	113.7	1,816.1	315.6	589.1
							886.8	49.7	570.6	2,699.4	201.4	913.0	3,368.9	210.4	913.0	110.5	1,458.0	210.4	476.1	110.5	2,836	210.4	860	143.4	2,392	210.4	619

Primary Energy

Cen Region	Cim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
		State	City	County			Heat	Cool	HW	Heat	Cool	HW	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW
							MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU	MBTU
Northeast	4A	PA	Philadelphia	Philadelphia	21,879,116	48.1%	40.9	8.1	37.5	115.1	27.6	98.0	164.1	28.8	60.9	6.0	78.7	28.8	29.8	6.0	73.4	28.8	36.9	7.9	86.3	28.8	31.5
Northeast	5A	MA	Boston	Suffolk	28,102,970	51.6%	48.0	4.5	41.7	138.6	17.8	63.9	190.9	18.6	63.9	6.4	82.3	18.6	31.8	6.4	85.4	18.6	33.0	8.2	100.5	18.6	33.6
Northeast	6A	ME	Bangor	Penobscot	4,515,671	8.3%	83.0	2.5	40.5	262.1	10.4	67.5	309.4	10.8	67.5	10.1	133.3	10.8	33.6	10.1	136.5	10.8	34.9	13.1	162.8	10.8	35.6
Total Pop Wgt Avg Arithmetic Average					54,497,757	100%	48.4	6.2	39.9	139.5	21.1	62.6	190.0	22.1	62.6	6.5	81.9	22.1	31.1	6.5	85.0	22.1	32.3	8.4	100.0	22.1	32.9
							65.9	3.5	41.1	200.5	14.1	65.7	250.2	14.7	65.7	8.2	107.8	14.7	32.7	8.2	112	14.7	34	10.7	132	14.7	35

Emission

Cen Region	Cim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
		State	City	County			Heat	Cool	HW	Heat	Cool	HW	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW	Heat	Heat	Cool	HW
							Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb	Lb
Northeast	4A	PA	Philadelphia	Philadelphia	21,879,116	48.1%	5,940.2	1,322.6	5,447.5	16,741.8	4,014.7	8,717.4	23,855.2	4,193.4	8,717.4	868.4	9,666.3	4,193.4	4,071.6	868.4	11,255.5	4,193.4	4,738.7	1,127.3	14,480.0	4,193.4	5,271.0
Northeast	5A	MA	Boston	Suffolk	28,102,970	51.6%	7,089.2	648.0	6,057.1	20,183.6	2,586.6	9,298.6	27,762.9	2,702.1	9,298.6	923.5	11,249.7	2,702.1	4,343.0	923.5	13,099.2	2,702.1	5,054.6	1,198.8	16,828.7	2,702.1	5,622.4
Northeast	6A	ME	Bangor	Penobscot	4,515,671	8.3%	12,062.4	392.4	5,893.4	38,114.4	1,598.9	9,821.3	44,993.7	1,574.9	9,821.3	1,462.9	18,231.7	1,574.9	4,599.4	1,462.9	21,229.2	1,574.9	5,351.9	1,899.9	27,273.2	1,574.9	5,954.3
Total Pop Wgt Avg Arithmetic Average					54,497,757	100%	7,040.0	895.2	5,798.6	20,287.6	3,070.7	9,108.6	27,621.8	3,207.4	9,108.6	946.1	11,192.5	3,207.4	4,255.3	946.1	13,032.7	3,207.4	4,952.5	1,228.1	16,743.2	3,207.4	5,508.9
							9,575.8	505.2	5,975.3	29,149.0	2,047.4	9,559.9	36,378.3	2,138.4	9,559.9	1,193.2	14,740.7	2,138.4	4,471.2	1,193.2	17,164	2,138.4	5,204	1,548.9	22,051	2,138.4	5,788

C-2 Midwest Region

Delivered Energy

Cen Region	Clim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)										
		State	City	County			Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Heat Mcf	Cool MWh	HW Mcf	Heat MWh	Heat Gal	Cool MWh	HW Gal	Heat MWh	Heat Gal	Cool MWh	HW Gal							
Midwest	4A	MO	Kansas	Jackson	12,501,407	19.3%	2.7	2.0	3.2	8.1	4.5	5.0	10.4	4.7	5.0	0.4	46.8	4.7	25.9	0.4	511.7	4.7	283.0	0.6	392.5	4.7	188.0							
Midwest	5A	IL	Chicago	Cook	39,992,232	61.8%	5.2	0.6	3.3	16.5	2.1	5.5	19.6	2.1	5.5	0.6	87.9	2.1	28.5	0.6	961.1	2.1	311.5	0.8	737.1	2.1	206.8							
Midwest	6A	MN	Minneapolis	Hennepin	12,213,811	18.9%	7.0	0.4	3.5	23.0	1.5	5.8	28.1	1.5	5.8	0.9	117.1	1.5	29.9	0.9	1,280.3	1.5	326.8	1.1	982.0	1.5	217.0							
Total					64,707,450	100%																												
Pop Wgt Avg Arithmetic Average							6.1	0.8	3.3	16.1	2.4	5.5	19.0	2.5	5.5	0.6	85.5	2.5	28.3	0.6	934.5	2.5	308.9	0.8	716.8	2.5	205.1							
							5.1	0.5	3.4	19.8	1.8	5.6	22.8	1.8	5.6	0.7	102.5	1.8	29.2	0.7	1,121	1.8	319	1.0	860	1.8	212							

Utility Cost

Cen Region	Clim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
		State	City	County			Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Heat \$	Cool \$	HW \$	Heat \$	Heat \$	Cool \$	HW \$	Heat \$	Heat \$	Cool \$	HW \$
Midwest	4A	MO	Kansas	Jackson	12,501,407	19.3%	266.4	212.3	324.4	796.1	470.9	510.5	1,021.9	491.8	510.5	43.1	511.5	491.8	316.8	43.1	976.9	491.8	530.7	56.0	1,109.2	491.8	528.4
Midwest	5A	IL	Chicago	Cook	39,992,232	61.8%	511.7	63.1	335.6	1,618.4	218.9	560.1	1,919.3	226.6	560.1	62.3	960.7	226.6	348.7	62.3	1,834.9	226.6	583.9	69.9	2,083.4	226.6	591.4
Midwest	6A	MN	Minneapolis	Hennepin	12,213,811	18.9%	689.2	40.1	357.6	2,253.0	155.9	588.5	2,556.9	162.9	588.5	83.8	1,279.8	162.9	365.8	83.8	2,444.4	162.9	612.6	108.7	2,775.5	162.9	610.0
Total					64,707,450	100%																					
Pop Wgt Avg Arithmetic Average							497.8	87.6	337.6	1,579.3	254.5	555.9	1,866.3	265.8	555.9	62.7	934.1	265.8	345.7	62.7	1,784.2	265.8	579.1	81.3	2,025.8	265.8	576.6
							51	1,935.7	186.4	574.3	2,238.1	194.7	574.3	73.0	1,120.2	194.7	357.2	73.0	2,140	194.7	596	94.8	2,420	194.7	596		

Primary Energy

Cen Region	Clim Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
		State	City	County			Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU
Midwest	4A	MO	Kansas	Jackson	12,501,407	19.3%	31.2	23.0	36.6	93.3	51.1	57.6	119.8	53.4	57.6	5.1	51.6	53.4	28.6	5.1	53.6	53.4	29.6	6.6	63.0	53.4	30.2
Midwest	5A	IL	Chicago	Cook	39,992,232	61.8%	60.0	6.9	37.8	189.7	23.6	63.1	225.0	24.6	63.1	7.3	96.9	24.6	31.4	7.3	100.7	24.6	32.6	9.5	118.4	24.6	33.2
Midwest	6A	MN	Minneapolis	Hennepin	12,213,811	18.9%	80.8	4.4	49.3	264.1	16.9	66.3	299.7	17.7	66.3	9.8	129.2	17.7	33.0	9.8	134.1	17.7	34.2	12.7	157.7	17.7	34.9
Total					64,707,450	100%																					
Pop Wgt Avg							58.3	9.5	38.1	185.1	27.6	62.7	218.8	28.9	62.7	7.3	94.3	28.9	31.2	7.3	97.9	28.9	32.3	9.5	115.1	28.9	32.9
Arithmetic Average							5.6	11.1	208.9	20.2	64.7	262.3	21.1	64.7	8.6	113.0	21.1	32.2	8.6	117	21.1	33	11.1	138	21.1	34	

Emission

Cen Region	Cim Zone	Main Heating Fuel Type		Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)				
						Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	
		State	County			Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	
Midwest	4A	MO	Kansas	Jackson	12,501,407	19.3%	4,540.7	3,351.7	5,317.3	13,568.8	7,434.8	8,368.4	17,416.9	7,765.5	8,368.4	734.8	7,057.4	7,765.5	3,905.7	734.8	8,217.7	7,765.5	4,545.7	953.8	10,557.4	7,765.5	5,056.3
Midwest	5A	IL	Chicago	Cook	39,992,232	61.8%	8,720.7	997.0	5,501.0	27,583.4	3,425.2	9,181.7	32,712.5	3,577.1	9,181.7	1,062.1	13,255.3	3,577.1	4,297.8	1,062.1	15,434.6	3,577.1	5,002.0	1,378.7	19,829.0	3,577.1	5,563.9
Midwest	6A	MN	Minneapolis	Hennepin	12,213,811	18.9%	11,746.8	632.9	5,861.7	38,406.0	2,461.6	8,647.6	43,579.5	2,571.8	8,647.6	1,427.9	17,654.7	2,571.8	4,506.9	1,427.9	20,561.9	2,571.8	5,247.7	1,853.5	26,416.1	2,571.8	5,637.2
Total					64,707,450	100%																					
Pop Wgt Avg Arithmetic Average							8,484.3	1,383.2	5,533.6	26,917.5	4,018.0	9,112.5	31,808.6	4,196.6	9,112.5	1,967.9	12,899.0	4,196.6	4,261.9	1,967.9	15,008.1	4,196.6	4,960.2	1,386.2	19,281.0	4,196.6	5,517.4
Geometric Average							8,113.8	1,318.2	5,391.1	25,991.7	3,943.4	8,914.6	30,146.0	3,974.5	8,914.6	1,245.0	15,457.0	3,974.5	4,403.4	1,245.0	17,998.0	3,974.5	5,125.0	1,616.1	23,123.0	3,974.5	5,701.4

C-3 South Region

Delivered Energy

	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
	State	City	County			Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh			
Northeast 2A	TX	Houston	Harris	30,898,043	31.6%	1.1	2.4	2.3	2.5	5.4	4.1	5.4	5.6	4.1	0.2	24.4	5.6	21.3	0.2	266.8	5.6	232.8	0.3	204.6	5.6	154.6
Northeast 3A	GA	Atlanta	Fulton	37,141,601	37.9%	2.2	1.3	3.0	5.4	3.5	4.7	9.9	3.7	4.7	0.4	44.4	3.7	24.5	0.4	485.4	3.7	267.7	0.5	372.3	3.7	177.8
Northeast 4A	TN	Nashville	Davidson	29,844,870	30.5%	3.5	1.4	2.7	10.4	3.7	4.9	14.6	3.8	4.9	0.5	65.4	3.8	25.2	0.5	715.1	3.8	275.4	0.7	548.4	3.8	182.9
Total				97,884,514	100%																					
Pop Wgt Avg						2.3	1.7	2.7	6.0	4.2	4.6	9.9	4.4	4.6	0.4	44.5	4.4	23.7	0.4	486.4	4.4	259.0	0.5	373.1	4.4	172.0
Arithmetic Average						2.3	1.7	2.7	6.1	4.2	4.6	10.0	4.4	4.6	0.4	44.7	4.4	23.7	0.4	489	4.4	259	0.5	375	4.4	172

Utility Cost

Cen Regic CIm Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
	State	City	County			Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Heat \$	Cool \$	HW \$	Heat \$	Heat \$	Cool \$	HW \$	Heat \$	Heat \$	Cool \$	HW \$
Northeast 2A	TX	Houston	Harris	30,898,043	31.6%	119.3	260.4	252.7	269.3	596.6	443.9	575.8	623.2	443.9	21.2	357.8	623.2	356.0	21.2	647.9	623.2	553.4	27.5	586.5	623.2	432.8
Northeast 3A	GA	Atlanta	Fulton	37,141,601	37.9%	236.2	146.7	321.7	573.8	388.7	511.7	1,047.8	405.9	511.7	38.7	651.2	405.9	409.5	38.7	1,179.0	405.9	636.6	50.2	1,067.3	405.9	497.9
Northeast 4A	TN	Nashville	Davidson	29,844,870	30.5%	374.9	149.5	295.4	1,099.7	406.5	526.7	1,543.4	424.6	526.7	55.5	959.1	424.6	421.2	55.5	1,736.7	424.6	654.8	72.9	1,572.1	424.6	512.1
Total				97,884,514	100%																					
Pop Wgt Avg						241.3	183.4	291.9	638.0	459.8	494.9	1,049.9	480.2	494.9	38.3	652.5	480.2	396.2	38.3	1,181.4	480.2	615.9	49.7	1,069.4	480.2	481.7
Arithmetic Average						305.1	148.1	308.5	836.7	397.6	519.2	1,296.6	415.2	519.2	47.1	805.1	415.2	415.4	47.1	1,458	415.2	646	61.1	1,320	415.2	505

Primary Energy

Cen Regic Cln Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)				Propane (with central AC)				Oil (with central AC)			
	State	City	County			Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU
Northeast 2A	TX	Houston	Harris	30,898,043	31.6%	12.9	27.1	26.8	29.2	62.1	47.2	62.4	64.9	47.2	2.3	26.9	64.9	23.5	2.3	27.9	64.9	24.4	3.0	32.9	64.9	24.8
Northeast 3A	GA	Atlanta	Fulton	37,141,601	37.9%	25.6	15.3	34.2	62.2	46.5	54.4	113.6	42.3	54.4	4.2	49.9	42.3	27.0	4.2	50.8	42.3	28.0	5.4	59.8	42.3	28.6
Northeast 4A	TN	Nashville	Davidson	29,844,870	30.5%	49.6	15.6	31.4	119.3	42.3	56.9	167.4	44.2	56.9	6.9	72.1	44.2	27.8	6.9	74.9	44.2	28.8	7.8	88.1	44.2	29.4
Total				97,884,514	100%																					
Pop Wgt Avg						26.2	19.1	31.0	69.2	47.9	52.6	113.9	50.0	52.6	4.2	49.1	50.0	26.1	4.2	50.9	50.0	27.1	5.4	59.9	50.0	27.6
Arithmetic Average						33.1	15.4	32.8	90.7	41.4	55.2	140.5	43.2	55.2	5.1	60.6	43.2	27.4	5.1	63	43.2	28	6.6	74	43.2	29

Emission

Gen Reg/Cen/Com Zone	Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
	State	City	County			Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb			
Northeast 2A	TX	Houston	Harris	30,898,043	31.6%	1,882.1	3,941.2	3,902.8	4,246.8	9,031.4	6,857.0	9,080.6	9,433.8	6,857.0	334.0	3,679.5	9,433.8	3,212.0	334.0	4,284.5	9,433.8	3,738.3	433.6	5,504.3	9,433.8	4,158.3
Northeast 3A	GA	Atlanta	Fulton	37,141,601	37.9%	3,724.1	2,221.1	4,969.9	9,048.1	5,883.4	7,894.1	16,523.7	6,143.9	7,894.1	699.6	6,696.5	6,143.9	3,694.6	699.6	7,796.3	6,143.9	4,289.9	791.2	10,016.0	6,143.9	4,763.0
Northeast 4A	TN	Nashville	Davidson	29,844,870	30.5%	5,898.4	2,262.9	4,562.4	17,341.3	6,154.0	8,136.2	24,339.0	6,427.8	8,136.2	975.1	9,862.3	6,427.8	3,900.2	975.1	11,483.8	6,427.8	4,422.8	1,135.9	14,753.3	6,427.8	4,919.6
Total				97,884,514	100%																					
Pop Wgt Avg						3,805.6	2,776.8	4,508.8	10,061.1	6,959.6	7,644.4	16,557.1	7,260.0	7,644.4	603.5	6,709.0	7,260.0	3,574.5	603.5	7,812.1	7,260.0	4,160.1	783.4	10,036.2	7,260.0	4,627.4
Arithmetic Average						4,811.3	2,242.0	4,766.2	13,194.7	6,018.7	8,020.2	20,431.4	6,285.9	8,020.2	742.3	8,278.9	6,285.9	3,747.4	742.3	9,640.0	6,285.9	4,361.0	963.6	12,385.0	6,285.9	4,851.0

C-4 West Region

Delivered Energy

		Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
							Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Heat Mcf	Cool MWh	HW Mcf	Heat MWh	Heat Gal	Cool MWh	HW Gal	Heat MWh	Heat Gal	Cool MWh	HW Gal
		State	City	County			Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Cool MWh	HW MWh	Heat MWh	Heat Mcf	Cool MWh	HW Mcf	Heat MWh	Heat Gal	Cool MWh	HW Gal	Heat MWh	Heat Gal	Cool MWh	HW Gal
West	2B	AZ	Phoenix	Maricopa	4,970,848	8.1%	0.9	2.9	2.1	2.1	6.5	4.0	4.5	6.8	4.0	0.2	20.3	6.8	20.5	0.2	222.0	6.8	224.0	0.2	170.2	6.8	148.8
West	3B	CA	Sacramento	Sacramento	29,832,102	48.7%	1.6	1.0	3.0	3.2	2.3	4.5	6.8	2.5	4.5	0.2	30.5	2.5	23.1	0.2	333.5	2.5	252.4	0.3	255.8	2.5	167.6
West	3C	CA	San Francisco	San Francisco	7,694,875	12.6%	1.5	0.8	3.2	3.0	1.9	4.5	6.3	2.0	4.5	0.2	28.3	2.0	23.1	0.2	309.4	2.0	252.4	0.2	237.3	2.0	167.6
West	4C	OR	Portland	Clackamas	7,844,547	12.8%	3.7	0.2	3.5	7.7	0.7	5.3	14.7	0.8	5.3	0.4	65.0	0.8	27.4	0.4	720.5	0.8	299.4	0.6	952.6	0.8	198.9
West	5B	CO	Denver	Denver	10,934,600	17.8%	5.2	0.5	3.4	16.8	1.6	5.4	20.2	1.7	5.4	0.6	90.7	1.7	28.1	0.6	991.7	1.7	307.1	0.8	760.6	1.7	203.9
Total					61,276,972	100%																					
Pop Wgt Avg							2.4	0.9	3.1	6.1	2.3	4.7	10.0	2.4	4.7	0.3	44.7	2.4	24.3	0.3	488.4	2.4	265.9	0.4	374.6	2.4	176.6
Arithmetic Average							3.4	0.5	3.4	9.2	1.4	5.1	13.7	1.5	5.1	0.4	61.6	1.5	26.2	0.4	674	1.5	286	0.5	517	1.5	190

Utility Cost

Cen Regic Cln Zone		Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
		State	City	County			Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$	Heat \$	Cool \$	HW \$			
West	2B	AZ	Phoenix	Maricopa	4,970,848	8.1%	100.6	345.0	243.1	228.7	771.4	452.7	494.7	805.7	452.7	18.0	209.2	805.7	221.5	18.0	522.5	805.7	513.1	23.4	506.9	805.7	442.3
West	3B	CA	Sacramento	Sacramento	29,832,102	48.7%	171.5	119.7	347.7	345.5	279.1	509.1	743.3	291.5	509.1	21.5	314.4	291.5	249.6	21.5	785.1	291.5	578.1	28.0	761.7	291.5	498.4
West	3C	CA	San Francisco	San Francisco	7,694,875	12.6%	162.7	92.6	361.5	324.8	223.0	509.1	689.7	233.0	509.1	20.0	291.7	233.0	249.6	20.0	728.4	233.0	578.1	26.0	706.7	233.0	498.4
West	4C	OR	Portland	Clackamas	7,844,547	12.8%	403.4	25.1	404.2	845.2	85.4	603.6	1,006.0	89.2	603.6	46.6	679.3	89.2	296.0	46.6	1,696.2	89.2	685.7	60.5	1,645.7	89.2	591.1
West	5B	CO	Denver	Denver	10,934,600	17.8%	563.8	55.4	393.4	1,834.5	190.0	619.6	2,210.4	198.4	619.6	67.8	934.9	198.4	303.6	67.8	2,334.6	198.4	703.3	88.0	2,265.0	198.4	606.2
Total					61,276,972	100%																					
Pop Wgt Avg							264.3	111.0	356.3	664.6	271.3	536.3	1,089.7	283.3	536.3	32.5	460.4	283.3	262.9	32.5	1,149.8	283.3	609.0	42.2	1,115.5	283.3	524.9
Arithmetic Average							376.6	57.7	386.4	1,001.5	166.1	577.4	1,502.1	173.5	577.4	44.8	635.3	173.5	283.1	44.8	1,586	173.5	656	58.2	1,539	173.5	505

Primary Energy

Cen Regic Cln Zone		Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
		State	City	County			Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU	Heat MBTU	Heat MBTU	Cool MBTU	HW MBTU
West	2B	AZ	Phoenix	Maricopa	4,970,848	8.1%	10.6	33.3	24.5	24.0	74.5	45.6	52.0	77.8	45.6	1.9	22.4	77.8	22.6	1.9	23.2	77.8	23.5	2.5	27.3	77.8	23.9
West	3B	CA	Sacramento	Sacramento	29,832,102	48.7%	18.0	11.6	35.0	36.6	27.0	51.2	78.1	28.2	51.2	2.3	33.6	28.2	25.5	2.3	34.9	28.2	26.4	2.9	41.1	28.2	26.9
West	3C	CA	San Francisco	San Francisco	7,694,875	12.6%	17.1	8.9	36.4	34.1	21.5	51.2	72.4	22.5	51.2	2.1	31.2	22.5	25.5	2.1	32.4	22.5	26.4	2.7	38.1	22.5	26.9
West	4C	OR	Portland	Clackamas	7,844,547	12.8%	42.4	2.4	40.7	88.8	8.2	60.7	168.7	8.6	60.7	4.9	72.7	8.6	30.2	4.9	75.5	8.6	31.4	6.4	88.8	8.6	31.9
West	5B	CO	Denver	Denver	10,934,600	17.8%	59.2	5.4	39.6	192.7	18.4	62.4	232.1	19.2	62.4	7.1	100.0	19.2	31.0	7.1	103.9	19.2	32.2	9.2	122.2	19.2	32.8
Total					61,276,972	100%																					
Pop Wgt Avg							27.8	10.7	35.9	69.8	26.2	54.0	114.3	27.4	54.0	3.4	49.3	27.4	26.8	3.4	51.2	27.4	27.9	4.4	60.2	27.4	28.4
Arithmetic Average							38.6	5.6	38.9	105.2	16.0	58.1	157.7	16.8	58.1	4.7	68.0	16.8	28.9	4.7	71	16.8	30	6.1	83	16.8	31

Emission

Cen Regic Cln Zone		Main Heating Fuel Type			Population	P.W.F.	Geothermal (with electric Aux Heater)			Heat Pump (with electric Aux Heater)			Electric (with central AC)			Natural Gas (with central AC)			Propane (with central AC)			Oil (with central AC)					
		State	City	County			Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb	Heat Lb	Cool Lb	HW Lb			
West	2B	AZ	Phoenix	Maricopa	4,970,848	8.1%	1,536.4	4,846.3	3,557.1	3,492.0	10,836.6	6,624.9	7,554.8	11,317.6	6,624.9	275.6	3,061.2	11,317.6	3,091.4	275.6	3,564.5	11,317.6	3,597.9	357.7	4,579.4	11,317.6	4,002.1
West	3B	CA	Sacramento	Sacramento	29,832,102	48.7%	2,618.6	1,681.7	5,088.5	5,322.3	3,921.2	7,449.9	11,350.8	4,094.8	7,449.9	329.0	4,599.4	4,094.8	3,483.5	329.0	5,355.6	4,094.8	4,054.2	427.1	6,880.4	4,094.8	4,508.7
West	3C	CA	San Francisco	San Francisco	7,694,875	12.6%	2,485.0	1,300.9	5,290.6	4,959.9	3,132.9	7,449.9	10,532.0	3,273.2	7,449.9	305.6	4,267.6	3,273.2	3,483.5	305.6	4,969.3	3,273.2	4,054.2	396.7	6,384.1	3,273.2	4,508.7
West	4C	OR	Portland	Clackamas	7,844,547	12.8%	6,160.6	352.4	5,915.1	12,907.4	1,199.1	8,832.6	24,525.1	1,252.5	8,832.6	711.4	9,937.7	1,252.5	4,131.9	711.4	11,571.6	1,252.5	4,808.9	923.5	14,866.1	1,252.5	5,349.1
West	5B	CO	Denver	Denver	10,934,600	17.8%	6,160.9	778.2	5,956.5	28,014.3	2,668.7	33,754.6	2,786.2	9,006.4	1,035.4	13,677.6	2,787.2	4,237.5	1,035.4	15,926.3	1,252.5	4,931.8	1,344.0	20,460.6	2,787.2	5,485.8	
Total					61,276,972	100%																					
Per Avg Arthropod Average					4,696.4	1,559.2	5,214.7	10,148.6	3,811.2	7,848.4	16,624.4	3,880.4	7,848.4	496.7	6,736.3	3,880.4	3,659.2	496.7	7,843.8	3,880.4	4,270.4	644.8	10,677.0	3,880.4	4,750.1		
					5,031.5	1,505.1	5,654.1	15,293.9	2,333.5	8,445.6	22,937.2	2,437.6	8,445.6	69.1	9,294.3	2,437.6	3,951.0	69.1	10,827.7	2,437.6	4,598	884.1	13,904	2,437.6	5,115		

